# SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

# **BIKE7 LUBRICATE QUICK WET**

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

: BIKE7 LUBRICATE QUICK WET Product name Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1 Relevant identified uses

Lubricant

### 1.2.2 Uses advised against

No uses advised against known

### 1.3. Details of the supplier of the safety data sheet

### Supplier of the safety data sheet

BIKE 7\*

Industrielaan 5B

B-2250 Olen

**2** +32 14 23 72 03

**4** +32 14 85 97 38

info@bike7.be

\*BIKE 7 is a registered trademark of Novatech International N.V.

### Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

**2** +32 14 85 97 37

**4** +32 14 85 97 38

info@novatech.be

### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	azard statements	
Flam. Liq.	category 2	5: Highly flammable liquid and vapour.	
Asp. Tox.	category 1	H304: May be fatal if swallowed and enters airways.	
Skin Irrit.	category 2	315: Causes skin irritation.	
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.	

### 2.2. Label elements







Contains: hydrocarbons, C7, n-alkanes, isoalkanes, cyclics.

Signal word	Danger
H-statements	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

H315 Causes skin irritation. Harmful to aquatic life with long lasting effects. H412

P-statements

If medical advice is needed, have product container or label at hand. P101

P102 Keep out of reach of children.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

P280 Wear protective gloves, protective clothing and eye protection/face protection.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Reason for revision: 2, 3, 8, 9, 12 Revision number: 0100

Publication date: 2015-03-02 Date of revision: 2021-07-17

BIG number: 55952 1/18

P264 Wash hands thoroughly after handling.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

# SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 01-2119475515-33	927-510-4	C≤20%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)	Constituent	
hydrocarbons, C6, isoalkanes, < 5% n- hexane 01-2119484651-34	931-254-9	C≤10%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent	
n-hexane 01-2119480412-44	110-54-3 203-777-6	C≤0.5%	Flam. Liq. 2; H225 Repr. 2; H361f Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411 STOT RE 2; H373: C≥5%, (CLP Annex VI (ATP 0))	(1)(2)(10)	Constituent	
cyclohexane 01-2119463273-41	110-82-7 203-806-2	C≤0.2%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	(1)(2)(10)	Constituent	M: 1 (Acute, ECHA)

<sup>(1)</sup> For H- and EUH-statements in full: see section 16

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

### After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

### 4.2. Most important symptoms and effects, both acute and delayed

### 4.2.1 Acute symptoms

### After inhalation:

No effects known.

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 2 / 18

<sup>(2)</sup> Substance with a Community workplace exposure limit

<sup>(10)</sup> Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

### After skin contact:

Tingling/irritation of the skin.

### After eye contact:

Redness of the eye tissue.

### After ingestion:

Risk of aspiration pneumonia. Vomiting. Diarrhoea. Abdominal pain. Headache.

#### 4.2.2 Delayed symptoms

No effects known.

### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

# SECTION 5: Firefighting measures

### 5.1. Extinguishing media

### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher. Major fire: Class B foam (not alcohol-resistant).

#### 5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed.

### 5.3. Advice for firefighters

### 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Do not move the load if exposed to heat. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

# SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment.

### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill. Try to reduce evaporation. Prevent soil and water pollution. Prevent spreading in sewers.

### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 7.1. Precautions for safe handling

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/ explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away. Observe normal hygiene standards. Keep container tightly closed. Do not discharge the waste into the drain.

### 7.2. Conditions for safe storage, including any incompatibilities

### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Provide for a tub to collect spills. Keep out of direct sunlight. Protect against frost. Keep container tightly closed.

### 7.2.2 Keep away from:

Reason for revision: 2, 3, 8, 9, 12

Revision number: 0100

Heat sources, ignition sources, oxidizing agents, reducing agents, (strong) acids, (strong) bases.

### 7.2.3 Suitable packaging material:

No data available

### 7.2.4 Non suitable packaging material:

Publication date: 2015-03-02 Date of revision: 2021-07-17

3 / 18

BIG number: 55952

No data available

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### 8.1.1 Occupational exposure

a) Occupational exposure limit values
If limit values are applicable and available these will be listed below.

Cyclohexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	700 mg/m <sup>3</sup>
n-Hexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	72 mg/m³

### Belgium

Cyclohexane	Time-weighted average exposure limit 8 h	100 ppm
	Time-weighted average exposure limit 8 h	350 mg/m³
n-Hexane	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	72 mg/m <sup>3</sup>

### The Netherlands

Cyclohexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	200 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	700 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	400 ppm
	Short time value (Public occupational exposure limit value)	1400 mg/m³
n-Hexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	72 mg/m <sup>3</sup>
	Short time value (Public occupational exposure limit value)	40 ppm
	Short time value (Public occupational exposure limit value)	144 mg/m³

### France

Cyclohexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	200 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	700 mg/m <sup>3</sup>
	Short time value (VL: Valeur non réglementaire indicative)	375 ppm
	Short time value (VL: Valeur non réglementaire indicative)	1300 mg/m <sup>3</sup>
n-Hexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	72 mg/m <sup>3</sup>

### Germany

Cyclohexan	Time-weighted average exposure limit 8 h (TRGS 900)	200 ppm
Time-weighted average exposure limit 8 h (TRGS 900)		700 mg/m <sup>3</sup>
n-Hexan	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	180 mg/m³

### UK

Cyclohexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	100 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	350 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	300 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1050 mg/m <sup>3</sup>
n-Hexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	20 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	72 mg/m <sup>3</sup>

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02 Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 4/18

## USA (TLV-ACGIH)

Cyclohexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	100 ppm
n-Hexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm

### b) National biological limit values

If limit values are applicable and available these will be listed below.

Cyclohexan (1,2-Cyclohexandiol (nach Hydrolyse))	,	150 mg/g Kreatinin	
Hexan (n-Hexan) (2,5-Hexandion plus 4,5-Dihydroxy-2-Hexanon (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende	5 mg/l	

### USA (BEI-ACGIH)

Cyclohexane (1,2-Cyclohexanediol)		50 mg/g creatinine	Nonspecific - Intended changes
n-Hexane (2,5-Hexanedione)	Urine: end of shift	0,5 mg/L	Without hydrolysis

### 8.1.2 Sampling methods

Product name	Test	Number
Cyclohexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
Cyclohexane	OSHA	1022
Cyclohexane	OSHA	7
n-Hexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
n-Hexane (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
n-Hexane (Volatile Organic compounds)	NIOSH	2549
n-Hexane	OSHA	2248
n-Hexane	OSHA	7

## $\bf 8.1.3$ Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

### 8.1.4 Threshold values

### **DNEL/DMEL - Workers**

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL Long-term systemic effects inhalation		2085 mg/m³	
	Long-term systemic effects dermal	300 mg/kg bw/day	

### hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL Long-term systemic effects inhalation		5306 mg/m³	
	Long-term systemic effects dermal	13964 mg/kg bw/day	

### n-hexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation		
	Long-term systemic effects dermal	11 mg/kg bw/day	

### cyclohexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	700 mg/m³	
	Acute systemic effects inhalation	1400 mg/m³	
	Long-term local effects inhalation	700 mg/m³	
	Acute local effects inhalation	1400 mg/m³	
	Long-term systemic effects dermal	2016 mg/kg bw/day	

<u>DNEL/DMEL - General population</u> hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	447 mg/m³	
	Long-term systemic effects dermal	149 mg/kg bw/day	
	Long-term systemic effects oral	149 mg/kg bw/day	

# hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL Long-term systemic effects inhalation		1131 mg/m³	
Long-term systemic effects dermal		1377 mg/kg bw/day	
, , , , , , , , , , , , , , , , , , ,		1301 mg/kg bw/day	
`.	•		-

### <u>n-hexane</u>

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL Long-term systemic effects inhalation		16 mg/m³	
Long-term systemic effects dermal		5.3 mg/kg bw/day	
	Long-term systemic effects oral	4 mg/kg bw/day	

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02 Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 5 / 18

cyclohexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL Long-term systemic effects inhalation		206 mg/m <sup>3</sup>	
Acute systemic effects inhalation		412 mg/m <sup>3</sup>	
Long-term local effects inhalation		206 mg/m <sup>3</sup>	
Acute local effects inhalation		412 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	1186 mg/kg bw/day	
	Long-term systemic effects oral	59.4 mg/kg bw/day	

### **PNEC**

cyclohexane

Compartments	Value	Remark
Fresh water	44.7 μg/l	
Fresh water (intermittent releases)	9 μg/l	
Marine water	4.47 μg/l	
Marine water (intermittent releases)	0.9 μg/l	
STP	3.24 mg/l	
Fresh water sediment	3.6 mg/kg sediment dw	
Marine water sediment	0.36 mg/kg sediment dw	
Soil	0.694 mg/kg soil dw	

### 8.1.5 Control banding

If applicable and available it will be listed below.

### 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

### c) Eye protection:

Protective goggles (EN 166).

### d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

mormation on Basic priyorear and	
Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	1.1 - 7.4 vol %
Flammability	Highly flammable liquid and vapour.
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 ℃
Kinematic viscosity	1 mm²/s ; 20 °C
Melting point	No data available in the literature
Boiling point	60 °C - 300 °C
Relative vapour density	No data available in the literature
Vapour pressure	190 hPa ; 20 °C
Solubility	Water ; insoluble
Relative density	0.84 ; 20 °C
Absolute density	840 kg/m³ ; 20 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	413 °C
Flash point	-20 °C
рН	Not applicable (non-soluble in water)

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02 Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 6 / 18

### 9.2. Other information

7; Butyl acetate Evaporation rate

# SECTION 10: Stability and reactivity

### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

 $Stable\ under\ normal\ conditions.$ 

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

### **Precautionary measures**

Keep away from naked flames/heat. Insufficient ventilation: take precautions against electrostatic charges. Insufficient ventilation: use spark-/ explosionproof appliances and lighting system. Insufficient ventilation: keep naked flames/sparks away.

### 10.5. Incompatible materials

Oxidizing agents, reducing agents, (strong) acids, (strong) bases.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

# SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### 11.1.1 Test results

### Acute toxicity

### **BIKE7 LUBRICATE QUICK WET**

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50		> 5840 mg/kg bw		Rat (male /	Read-across	
					female)		
Dermal	LD50		> 2800 mg/kg bw	24 h	Rat (male /	Read-across	
					female)		
Inhalation (vapours)	LC50	Equivalent to OECD	> 23.3 mg/l air	4 h	Rat (male /	Read-across	
		403			female)		

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	> 16750 mg/kg bw		Rat (male)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	259.354 mg/l	4 h	Rat (male)	Read-across	

n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	16000 mg/kg bw		Rat (male /	Experimental value	
		401			female)		
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 17.6 mg/l air	24 h	Rat (male)	Experimental value	

cyclohexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	> 5000 mg/kg bw		Rat (male /	Experimental value	
		401			female)		
Dermal	LD50	Equivalent to OECD	> 2000 mg/kg bw		Rabbit (male /	Experimental value	
		402			female)		
Inhalation (vapours)	LC50	Equivalent to OECD	> 19.07 mg/l	4 h	Rat (male /	Experimental value	
' '	1	403			female)		

### Conclusion

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02 Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 7 / 18

Not classified for acute toxicity

### Corrosion/irritation

### **BIKE7 LUBRICATE QUICK WET**

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye	Not irritating			7 days	Rabbit	Read-across	Single treatment
Skin	Irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye		Equivalent to OECD 405	72 h	72 hours	Rabbit	Read-across	
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Experimental value	

n-hexane

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		72 hours	Rabbit	Read-across	
Skin	Irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Read-across	

cyclohexane

Route of exposure	Result	Method	Exposure time	Time point	- •	Value determination	Remark
Eye	Slightly irritating	Equivalent to OECD 405		1 hour	Rabbit	Experimental value	
Skin	Not irritating	Equivalent to EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Irritating; category 2					Annex VI	

### Conclusion

Causes skin irritation.

Not classified as irritating to the respiratory system

Not classified as irritating to the eyes

### Respiratory or skin sensitisation

### BIKE7 LUBRICATE QUICK WET

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Observation time	Species	Value determination	Remark
				point			
Skin	Not sensitizing	Equivalent to OECD 406		24; 48 hours	Guinea pig (male / female)	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429		Mouse (male / female)	Read-across	

n-hexane

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429			Mouse	Read-across	

cyclohexane

Route of exposure	Result	Method	•	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	EU Method B.6			Guinea pig (male / female)	Experimental value	

### <u>Conclusion</u>

Not classified as sensitizing for inhalation Not classified as sensitizing for skin

### Specific target organ toxicity

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 8 / 18

### **BIKE7 LUBRICATE QUICK WET**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	12350 mg/m³ air			26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation (vapours)	LOAEL	Equivalent to OECD 413	1650 mg/m³ air	Central nervous system		26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	10504 mg/m <sup>3</sup> air			13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 413	31652 mg/m <sup>3</sup> air	Liver; kidney	-	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across

n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
								determination
Oral (stomach tube)	NOAEL	Subchronic toxicity test	567 mg/kg bw/day - 1135 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rat (male)	Experimental value
Oral (stomach tube)	LOAEL	Subchronic toxicity test	3956 mg/kg bw/day	Central nervous system	neurotoxic effects	17 weeks (5 days / week)	Rat (male)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	LOAEC	Subchronic toxicity test	3000 ppm	Central nervous system	neurotoxic effects	16 weeks (daily)	Rat (male)	Experimental value
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Annex VI

cyclohexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral								Data waiving
Dermal								Data waiving
Inhalation (vapours)	NOAEC	EPA OPPTS 870.3465	7000 ppm			13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value
Inhalation (vapours)	NOAEC	EPA OPPTS 870.3465	500 ppm	Central nervous system	No effect	6 h	Rat (male / female)	Experimental value

## Conclusion

Not classified for subchronic toxicity

### Mutagenicity (in vitro)

### **BIKE7 LUBRICATE QUICK WET**

activation

No (test)data on the mixture available

Judgement is based on the relevant ingredients <u>hydrocarbons</u>, C7, n-alkanes, isoalkanes, cyclics

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 9 / 18

<u>hexane</u>					
Result	Method	Test substrate	Effect	Value determination	Remark
Negative	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
<u>lohexane</u>		•		•	
Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	

### Mutagenicity (in vivo)

### **BIKE7 LUBRICATE QUICK WET**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Result	Method	Exposure time	Test substrate	Organ	Value determination
	Negative (Inhalation (vapours))	Equivalent to OECD	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value
		475				
n-h	<u>exane</u>					

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))		8 weeks (6h / day, 5 days / week)	Mouse (male)		Experimental value
	ļ	days / week)			

cyclohexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value
	475				

### $\underline{\textbf{Conclusion}}$

Not classified for mutagenic or genotoxic toxicity

### Carcinogenicity

### **BIKE7 LUBRICATE QUICK WET**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

<u>hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</u>

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation								Data waiving
Dermal								Data waiving
Oral								Data waiving

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
	exposure								
	Inhalation	NOAEC	Equivalent to	9016 ppm	104 weeks (6h / day,	Rat (male /	No carcinogenic		Experimental value
	(vapours)		OECD 451		5 days / week)	female)	effect		
<u>n-h</u>	<u>exane</u>	-			-		-	-	

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	3000 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	No carcinogenic effect		Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	Tumor formation	Liver	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (male)	No carcinogenic effect		Read-across

### Conclusion

Not classified for carcinogenicity

### Reproductive toxicity

### BIKE7 LUBRICATE QUICK WET

No (test)data on the mixture available Judgement is based on the relevant ingredients

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02 Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 10 / 18

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Exposure time	Species	Effect	- 0-	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	31680 mg/m³ air	10 days (6h / day)	Mouse	No effect		Read-across
Maternal toxicity	NOAEL	Equivalent to OECD 414	10560 mg/m³ air	10 days (6h / day)	Rat (female)	No effect		Read-across
	LOAEL	Equivalent to OECD 414	31680 mg/m³ air	10 days (6h / day)	Rat (female)	Lung tissue affection/degen eration	Lungs	Read-across
Effects on fertility	NOAEL (P/F1)	Equivalent to OECD 416	31680 mg/m³ air		Rat (male / female)	No effect		Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	> 7000 ppm	10 days (6h / day)	Rat	No effect		Read-across
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	2000 ppm	10 days (6h / day)	Rat (female)	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm		Rat (male / female)	No effect		Read-across

n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	3000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
	LOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm	≥ 13 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value				
								determination				
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	7000 ppm	10 days (6h / day)	Rat	No effect		Experimental value				
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	500 ppm - 2000 ppm	10 days (6h / day)	Rat	No effect		Experimental value				
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	500 ppm - 2000 ppm	> 11 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value				

### Conclusion

Not classified for reprotoxic or developmental toxicity

### Aspiration hazard

May be fatal if swallowed and enters airways.

### **Toxicity other effects**

### BIKE7 LUBRICATE QUICK WET

Classification is based on the relevant ingredients

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
								determination
	NOAEC	Equivalent to	9000 ppm	Central nervous	Overall effects	13 weeks (6h /	Rat (male /	Experimental
		OECD 424		system		day, 5 days /	female)	value
						week)		Inhalation
cyc	lohexane							

, С	опсканс							
	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
								determination
	NOAEC		2000 ppm		neurotoxic effects	6 h	Rat (male)	Experimental
١								value

### Chronic effects from short and long-term exposure

**BIKE7 LUBRICATE QUICK WET** 

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 11 / 18

No effects known.

### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

# SECTION 12: Ecological information

### 12.1. Toxicity

### BIKE7 LUBRICATE QUICK WET

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Total Borra, C7, 11 directics, 130directics, excites										
	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination		
Acute toxicity fishes	LL50	OECD 203	> 13.4 mg/l WAF	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration		
Acute toxicity crustacea	EL50	OECD 202	3.0 mg/l WAF	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP		
Toxicity algae and other aquatic plants	EL50	OECD 201	13 mg/l WAF	96 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Read-across; GLP		
Long-term toxicity fish	NOELR		1.534 mg/l	28	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration		
Toxicity aquatic micro- organisms	EL50		26.81 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth rate		

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		18.27 mg/l	96 h	Oncorhynchus mykiss	Fresh water	QSAR
Acute toxicity crustacea	EL50		31.9 mg/l	48 h	Daphnia magna	Fresh water	QSAR
Toxicity algae and other aquatic plants	EL50		13.56 mg/l	72 h	Pseudokirchneri ella subcapitata	Fresh water	QSAR
Long-term toxicity fish	NOELR		4.089 mg/l	28 day(s)	Oncorhynchus mykiss	Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOELR		7.138 mg/l	21 day(s)	Daphnia magna	Fresh water	QSAR

 ${\it Classification\ of\ this\ substance\ is\ debatable\ as\ it\ does\ not\ correspond\ to\ the\ conclusion\ from\ the\ test}$ 

n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		12.51 mg/l	96 h	Oncorhynchus mykiss		Fresh water	Estimated value; Lethal
Acute toxicity crustacea	EL50		21.85 mg/l	48 h	Daphnia magna		Fresh water	Estimated value; Locomotor effect
Toxicity algae and other aquatic plants	EL50		9.285 mg/l	72 h	Pseudokirchneri ella subcapitata		Fresh water	Estimated value; Growth rate
Long-term toxicity fish	NOELR		2.8 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	Estimated value; Growth rate
Long-term toxicity aquatic crustacea	NOELR		4.888 mg/l	21 day(s)	Daphnia magna		Fresh water	Estimated value; Reproduction
Toxicity aquatic micro- organisms	EL50		48.39 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth

cyclohexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	4.53 mg/l	96 h	Pimephales promelas	Flow- through system	Fresh water	Experimental value; Measured concentration
Acute toxicity crustacea	EC50	Equivalent to OECD 202	0.9 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	EC50	Equivalent to OECD 201	9.317 mg/l	72 h	Pseudokirchneri ella subcapitata			Experimental value; Growth rate
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea								Data waiving
Toxicity aquatic micro- organisms	IC50		29 mg/l	15 h	Aerobic micro- organisms			Experimental value; Oxygen consumption

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 12 / 18

### Conclusion

Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

В	io	d	egi	rac	la	tic	n	wa	iter	
---	----	---	-----	-----	----	-----	---	----	------	--

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Experimental value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

### **Biodegradation water**

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Read-across

n-hexane

### **Biodegradation water**

Method	Value	Duration	Value determination
OECD 301F	98 %; Oxygen consumption	28 day(s)	Read-across

**Biodegradation soil** 

Method	Value	Duration	Value determination
			Data waiving

cyclohexane

### **Biodegradation water**

Method	Value	Duration	Value determination
OECD 301F	77 %; Oxygen consumption	28 day(s)	Experimental value

Half-life soil (t1/2 soil)

Method		Primary degradation/mineralisation	Value determination
28 day(s) - 180 day(s)			Literature study

### Conclusion

#### Water

Contains readily biodegradable component(s)

### 12.3. Bioaccumulative potential

**BIKE7 LUBRICATE QUICK WET** 

## Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

### Log Kow

Method	Remark	Value	Temperature	Value determination		
		> 3				

hydrocarbons, C6, isoalkanes, < 5% n-hexane

### **BCF** fishes

Parameter	Method	Value	Duration	Species	Value determination	
BCF		501.187		Pimephales promelas	Calculated value	
og Kow						

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		3.34	20 °C	Read-across

# <u>n-hexane</u>

# **BCF** fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	Other	501.187		Pimephales promelas	QSAR

# Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		4	20 °C	Experimental value

# cyclohexane

## BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		167 l/kg; Fresh		Pimephales promelas	QSAR
		weight			

### Log Kow

Method	Remark	Value	Temperature	Value determination
			25 °C	Experimental value

### Conclusion

Contains bioaccumulative component(s)

# 12.4. Mobility in soil

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02
Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 13 / 18

### hydrocarbons, C6, isoalkanes, < 5% n-hexane

### (log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	Calculated value

### Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	93.6 %	0 %	2.1 %	0.5 %	3.8 %	Calculated value

### n-hexane

### (log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	QSAR

### cyclohexane

### (log) Koc

Parameter	Method	Value	Value determination
log Koc		2.89	Calculated value

#### <u>Conclusion</u>

Contains component(s) that adsorb(s) into the soil

Contains component(s) with potential for mobility in the soil

### 12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

### 12.7. Other adverse effects

#### **BIKE7 LUBRICATE QUICK WET**

### Greenhouse gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

cyclohexane

### Groundwater

Groundwater pollutant

### SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

### 13.1.1 Provisions relating to waste

### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 06\* (waste engine, gear and lubricating oils: synthetic engine, gear and lubricating oils). Depending on branch of industry and production process, also other waste codes may be applicable.

### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

### 13.1.3 Packaging/Container

### **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

# **SECTION 14: Transport information**

### Road (ADR)

14.1. UN number	
UN number	3295
14.2. UN proper shipping name	
Proper shipping name	hydrocarbons, liquid, n.o.s.
14.3. Transport hazard class(es)	
Hazard identification number	33
Class	3
Classification code	F1

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 14 / 18

BIKE7 LUBRIC	CATE QUICK WET
.4. Packing group	
Packing group	II
Labels	3
1.5. Environmental hazards	
Environmentally hazardous substance mark	no
1.6. Special precautions for user	
Special provisions	640D
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
Limited quantities	
	liquids. A package shall not weigh more than 30 kg. (gross mass)
(RID)	
.1. UN number	
UN number	3295
.2. UN proper shipping name	P   T
Proper shipping name	hydrocarbons, liquid, n.o.s.
	ilyarocarbons, ilquia, il.o.s.
.3. Transport hazard class(es)	
Hazard identification number	33
Class	3
Classification code	F1
.4. Packing group	•
Packing group	li .
	··
Labels	3
.5. Environmental hazards	
Environmentally hazardous substance mark	no
.6. Special precautions for user	
Special provisions	640D
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
quantities	liquids. A package shall not weigh more than 30 kg. (gross mass)
	manus. A package shall hot weigh more than 30 kg. (gross indss)
d waterways (ADN)	
.1. UN number	
UN number	3295
	10200
.2. UN proper shipping name	hydrocarbons liquid nos
Proper shipping name	hydrocarbons, liquid, n.o.s.
.3. Transport hazard class(es)	1
Class	3
Classification code	F1
.4. Packing group	
Packing group	li .
	···
Labels	3
.5. Environmental hazards	
Environmentally hazardous substance mark	no
.6. Special precautions for user	
Special provisions	640D
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
Elimited quantities	liquids. A package shall not weigh more than 30 kg. (gross mass)
	inquisor in publicage shall not weight more than boings (g. oss mass)
IMDG/IMSBC)	
. <u>1. UN number</u>	
UN number	3295
.2. UN proper shipping name	
Proper shipping name	hydrocarbons, liquid, n.o.s. (cyclohexane)
	, a. coa. ac. a,q a.a, mois. (cyclonexalle)
.3. Transport hazard class(es)	T <sub>a</sub>
Class	3
.4. Packing group	
Packing group	II
Labels	3
.5. Environmental hazards	•
Marine pollutant	_
·	lno.
Environmentally hazardous substance mark	no
.6. Special precautions for user Special provisions	
	Combination packagings: not more than 1 liter per inner packaging for
Special provisions	
Special provisions Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
Special provisions Limited quantities7. Maritime transport in bulk according to IMO instruments	liquids. A package shall not weigh more than 30 kg. (gross mass)
Special provisions Limited quantities  .7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78	
Special provisions Limited quantities  .7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78	liquids. A package shall not weigh more than 30 kg. (gross mass)
Special provisions Limited quantities  -7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78  CAO-TI/IATA-DGR)	liquids. A package shall not weigh more than 30 kg. (gross mass)
Special provisions Limited quantities  .7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78  CAO-TI/IATA-DGR)  .1. UN number	liquids. A package shall not weigh more than 30 kg. (gross mass)  Not applicable, based on available data
Special provisions Limited quantities  .7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78  CAO-TI/IATA-DGR)  .1. UN number  UN number	liquids. A package shall not weigh more than 30 kg. (gross mass)
Special provisions Limited quantities  1.7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78  ICAO-TI/IATA-DGR)  1.1. UN number UN number  UN proper shipping name	Not applicable, based on available data  3295
Limited quantities  1.7. Maritime transport in bulk according to IMO instruments Annex II of MARPOL 73/78  ICAO-TI/IATA-DGR)  1.1. UN number	Not applicable, based on available data

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 15 / 18

14.3. Transport hazard class(es)	
Class	3
14.4. Packing group	
Packing group	II
Labels	3
14.5. Environmental hazards	
Environmentally hazardous substance mark	no
14.6. Special precautions for user	
Special provisions	A3
Special provisions	A324
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	11

# SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
21 %	

### REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

and use of certain dangerous	substances, mixtures and articles.	
	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics     hydrocarbons, C6, isoalkanes, < 5% n-hexane     n-hexane     cyclohexane	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in:  — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,  — tricks and jokes,  — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,  2. Articles not complying with paragraph 1 shall not be placed on the market.  3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  — can be used as fuel in decorative oil lamps for supply to the general public, and,  — present an aspiration hazard and are labelled with H304,  4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";  b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";  c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics     hydrocarbons, C6, isoalkanes, < 5% n-hexane     n-hexane     cyclohexane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:  — metallic glitter intended mainly for decoration,  — artificial snow and frost,  — "whoopee" cushions,  — silly string aerosols,  — imitation excrement,  — horns for parties,  — decorative flakes and foams,  — artificial cobwebs,  — stink bombs.  2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  "For professional users only".  3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.  4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· cyclohexane	Cyclohexane	Shall not be placed on the market for the first time after 27 June 2010, for supply to the general public, as a constituent of neoprene-based contact adhesives in concentrations equal to or greater than 0,1 % by weight in package sizes greater than 350 g.     Neoprene-based contact adhesives containing cyclohexane and not conforming to paragraph 1 shall not be placed on the market for supply to the general public after 27
acom for revisions 2, 2, 0, 12		Dublication data: 2015 02 02

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 16 / 18

		December 2010.  3. Without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that neoprene-based contact adhesives containing cyclohexane in concentrations equal to or greater than 0,1 % by weight that are placed on the market for supply to the general public after 27 December 2010 are visibly, legibly and indelibly marked as follows:  "— This product is not to be used under conditions of poor ventilation.  — This product is not to be used for carpet laying."
cyclohexane  following (a) subst following (EC) No 3 — carcin cell muta 2, but ex due to et exposure — reprobut excludue to et inhalatio — skin si — skin ci skin irrita — seriou irritant c (b) subst (EC) No 3 Parliame (c) subst (EC) No 3 specified and i of ti listed in. The ancil and 8 of mixtures whether	ng points: stances classified as any of the ng in Part 3 of Annex VI to Regulation 1272/2008: nogen category 1A, 1B or 2, or germ tagen category 1A, 1B or excluding any such substances classified effects only following re by inhalation oductive toxicant category 1A, 1B or 2 luding any such substances classified effects only following exposure by on sensitiser category 1, 1A or 1B corrosive category 1, 1A, 1B or 1C or tant category 2 rus eye damage category 1 or eye category 2 stances listed in Annex II to Regulation 1223/2009 of the European ent and of the Council stances listed in Annex IV to Regulation 1223/2009 for which a condition is di in at least one of the columns g, h the table in that Annex (d) substances a Appendix 13 to this Annex. cillary requirements in paragraphs 7 f column 2 of this entry apply to all es for use for tattooing purposes, er or not they contain a substance within points (a) to (d) of this column of	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

National legislation Belgium
BIKE7 LUBRICATE QUICK WET

No data available

# National legislation The Netherlands BIKE7 LUBRICATE QUICK WET

	Waterbezwaarlijkheid	A (3); Algemene Beoordelingsmethodiek (ABM)			
<u>n</u>	n-hexane				
	SZW - Lijst van voor de	n-hexaan; Opgenomen in SZW-lijst van voor de voortplanting giftige stoffen (vruchtbaarheid); 2			
	voortplanting giftige stoffen				
	(vruchtbaarheid)				

National legislation France
BIKE7 LUBRICATE QUICK WET

No data available

<u>n-hexane</u>

Catégorie toxique pour la	n-Hexane; R2
reproduction	

# National legislation Germany BIKE7 LUBRICATE QUICK WET

	Lagerklasse (TRGS510)	3: Entzündbare Flüssigkeiten		
	WGK	2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017		
<u>h</u>	ydrocarbons, C7, n-alkanes, isoall	kanes, cyclics		
	TA-Luft	5.2.5/I		
hydrocarbons, C6, isoalkanes, < 5% n-hexane				
	TA-Luft	5.2.5/I		
<u>n-hexane</u>				
	TA-Luft	5.2.5/I		
		n-Hexan; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden		
<u>cyclohexane</u>				
	TA-Luft	5.2.5/I		

# National legislation United Kingdom BIKE7 LUBRICATE QUICK WET

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02

Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 17 / 18

No data available

Other relevant data
BIKE7 LUBRICATE QUICK WET

No data available

<u>n-hexane</u>

TLV - Skin absorption n-Hexane; Skin; Danger of cutaneous absorption

### 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

### SECTION 16: Other information

### Full text of any H- and EUH-statements referred to under section 3:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

(\*) INTERNAL CLASSIFICATION BY BIG

ΔDI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE Acute Toxicity Estimate

Classification, labelling and packaging (Globally Harmonised System in Europe) CLP (EU-GHS)

**Derived Minimal Effect Level DMEL** DNEL Derived No Effect Level EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

Lethal Concentration 50 % LC50

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration

**OECD** Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic **PNEC** Predicted No Effect Concentration STP Sludge Treatment Process

very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-03-02 Date of revision: 2021-07-17

Revision number: 0100 BIG number: 55952 18 / 18