SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2015/830

BIKE7 E-CARE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

: BIKE7 F-CARE Product name

Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

1.2.2 Uses advised against

No uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

BIKE 7*

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@tec7.be

*BIKE 7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

2 +32 14 85 97 37

4 +32 14 85 97 38

info@tec7.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	zard statements	
Aerosol	category 1	222: Extremely flammable aerosol.	
Aerosol	category 1	229: Pressurised container: May burst if heated.	

2.2. Label elements



Signal word Danger

H-statements H222

Extremely flammable aerosol.

Pressurised container: May burst if heated. H229

P-statements

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source. P211

P251 Do not pierce or burn, even after use.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be

© BIG vzw

Reason for revision: 3.2; 5; 15 Revision number: 0503

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG) Publication date: 2007-10-23 Date of revision: 2019-05-06

1/13

Product number: 45574

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119457273-39	918-481-9	C≤30%	Asp. Tox. 1; H304	(1)(10)	Constituent
white mineral oil (petroleum) 01-2119487078-27	8042-47-5 232-455-8	C≤20%	Asp. Tox. 1; H304	(1)(2)(10)	Constituent
butane 01-2119474691-32	106-97-8 203-448-7	C≤40%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
propane 01-2119486944-21	74-98-6 200-827-9	C≤30%	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant

⁽¹⁾ For H-statements in full: see heading 16

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General

If you feel unwell, seek medical advice.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact

Rinse with water. Do not apply (chemical) neutralizing agents without medical advice. Take victim to a doctor if irritation persists.

After eve contact:

Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply (chemical) neutralizing agents without medical advice. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Do not apply (chemical) neutralizing agents without medical advice. Consult a doctor/medical service if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

EXPOSURE TO HIGH CONCENTRATIONS: Headache. Vomiting. Abdominal pain. Disturbances of consciousness.

After skin contact:

No effects known.

After eye contact:

Redness of the eye tissue.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

 $Small\ fire: Quick-acting\ ABC\ powder\ extinguisher,\ Quick-acting\ BC\ powder\ extinguisher.$

5.1.2 Unsuitable extinguishing media:

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam.

Major fire: Water (water can be used to control jet flame), Foam.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23

Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 2 / 13

⁽²⁾ Substance with a Community workplace exposure limit

⁽¹⁰⁾ Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2. Environmental precautions

Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Keep out of direct sunlight. Fireproof storeroom. Meet the legal requirements.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Belgium

Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m³
	Short time value	10 mg/m ³
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm
	Short time value	980 ppm
	Short time value	2370 mg/m ³

The Netherlands

Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure	5 mg/m³
	limit value)	

France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non	800 ppm
	réglementaire indicative)	

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23

Revision number: 0503 Product number: 45574 3 / 13

Date of revision: 2019-05-06

Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m³

Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m³
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³
Weißes Mineralöl (Erdöl)	Time-weighted average exposure limit 8 h (TRGS 900)	5 mg/m³

UK

Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m³
Short time value (Workplace exposure limit (EH40/2005))	750 ppm
Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m³

USA (TLV-ACGIH)

Butane, all isomers	Short time value (TLV - Adopted Value)	1000 ppm
Mineral oil, pure, highly and severely refined	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m³ (I)

⁽I): Inhalable fraction

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

Product name	Test	Number
Oil Mist (Mineral)	NIOSH	5026

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

If applicable and available it will be listed below.

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

${\bf 8.2.2\ Individual\ protection\ measures,\ such\ as\ personal\ protective\ equipment}$

Observe normal hygiene standards. Do not eat, drink or smoke during work.

<u>a) Respiratory protection:</u>

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index
nitrile rubber	> 480 minutes	0.35 mm	Class 6

c) Eye protection:

Protective goggles.

d) Skin protection:

Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	No data available
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid
Kinematic viscosity	1 mm²/s ; 20 °C ; Liquid
Melting point	No data available
Boiling point	187 °C - 300 °C ; Liquid

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23
Date of revision: 2019-05-06

 Revision number: 0503
 Product number: 45574
 4 / 13

Evaporation rate	0.04 ; Butyl acetate ; Liquid
Relative vapour density	No data available
Vapour pressure	8530 hPa ; 20 °C
Solubility	Water ; insoluble
Relative density	0.81 ; 20 °C ; Liquid
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Flash point	Not applicable
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

9.2. Other information

Absolute density	810 kg/m³ ; 20 °C ; Liquid	

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

11.1.1 Test results

Acute toxicity

BIKE7 E-CARE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	> 5000 mg/kg bw		Rat (male /	Read-across	
		401			female)		
Dermal	LD50	Equivalent to OECD	> 3160 mg/kg bw	24 h	Rabbit (male /	Read-across	
		402			female)		
Inhalation (aerosol)	LC50	Equivalent to OECD	> 5.6 mg/l	4 h	Rat (male)	Read-across	
, ,		403	_				

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50		> 2000 mg/kg bw		Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5 mg/l		Rat (male / female)	Read-across	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

BIKE7 E-CARE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Reason for revision: 3.2; 5; 15

Publication date: 2007-10-23

Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 5 / 13

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating	OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

white mineral oil (petroleum)

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit		Single treatment without rinsing
Skin	Not irritating	Equivalent to OECD 404	24 week(s)	24; 72 hours	Rabbit	Read-across	

Conclusion

Not classified as irritating to the skin Not classified as irritating to the eyes

Respiratory or skin sensitisation

BIKE7 E-CARE

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406	24; 48 hours	Guinea pig (female)	Read-across	

white mineral oil (petroleum)

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406	48 hours	Guinea pig (male)	Read-across	

Conclusion

Not classified as sensitizing for skin Not classified as sensitizing for inhalation

Specific target organ toxicity

BIKE7 E-CARE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Route of	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
exposure								determination
Oral (stomach tube)	NOAEL	Equivalent to OECD 422	≥ 1000 mg/kg bw/day		No effect		Rat (male / female)	Read-across
Dermal								Data waiving
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	≥ 2200 mg/m³ air			14 weeks (6h / day, 5 days / week)	Rat (female)	Read-across

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Oral (diet)	NOAEL	OECD 453	≥ 1200 mg/kg bw/day		No effect	24 month(s)	Rat (male / female)	Read-across
Dermal	NOAEL systemic effects	OECD 411	≥ 2000 mg/kg bw/day		No adverse systemic effects	13 weeks (daily)	Rat (male / female)	Read-across
Inhalation (aerosol)	l	Equivalent to OECD 412	50 mg/m³	Lungs		4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

BIKE7 E-CARE

No (test)data on the mixture available

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23

Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 6/13

white mineral oil (petroleum)

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	

Mutagenicity (in vivo)

BIKE7 E-CARE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD		Rat (male)		Read-across
	478				

white mineral oil (petroleum)

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow	Read-across

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

BIKE7 E-CARE

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
Ī		NOAEC	Equivalent to OECD 453	≥ 2200 mg/m³ air	105 weeks (6h / day, 5 days / week)	Rat (female)	No carcinogenic effect		Read-across

white mineral oil (petroleum)

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	- 0-	Value determination
Dermal	NOEL	OECD 453	≥ 75 µl/week	104 weeks (3 times / week)	Mouse (male)	No carcinogenic effect		Read-across
Oral	NOAEL	OECD 453	≥ 1200 mg/kg bw/day	24 month(s)	Rat (male / female)	No carcinogenic effect		Read-across

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

BIKE7 E-CARE

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

	Parameter	Method	Value	Exposure time	Species	Effect	0	Value determination
Developmental toxicity	NOAEC		≥ 1575 mg/m³	10 days (6h / day)	Rat (female)	No effect	l	Experimental value
Maternal toxicity	NOAEL	Equivalent to OECD 414	≥ 5220 mg/kg bw/day	10 day(s)	Rat	No effect	l	Experimental value

white mineral oil (petroleum)

	Parameter	Method	Value	Exposure time	Species	Effect	1 0	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	> 5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Read-across
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	> 5000 mg/kg bw/day	14 days (gestation, daily)	Rat	No effect		Read-across
Effects on fertility (Dermal)	NOAEL	Equivalent to OECD 415	≥ 2000	≥ 13 weeks (5 days / week)	Rat (male / female)	No effect		Read-across

Not classified for reprotoxic or developmental toxicity

Toxicity other effects

BIKE7 E-CARE

No (test)data on the mixture available

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23 Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 7 / 13

<u>hydrocarbons</u>, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Parameter	Method	Value	Organ	Effect	Exposure time	 Value
						determination
			Skin	Skin dryness or		Literature study
				cracking		Skin

Chronic effects from short and long-term exposure

BIKE7 E-CARE

No effects known.

SECTION 12: Ecological information

12.1. Toxicity

BIKE7 E-CARE

No (test)data on the mixture available

Judgement of the mixture is based on the relevant ingredients hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Tyurocarbons, C10-C15, 11-aikane	1	1	 					
	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt	Value determination
							water	
Acute toxicity fishes	LL50	OECD 203	> 1000 mg/l	96 h	Oncorhynchus	Semi-static	Fresh water	Experimental value;
					mykiss	system		GLP
Acute toxicity crustacea	EL50	OECD 202	> 1000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value;
								GLP
Toxicity algae and other	NOELR	OECD 201	> 1000 mg/l	72 h	Pseudokirchneri	Static system	Fresh water	Experimental value;
aquatic plants					ella subcapitata			GLP
Toxicity aquatic micro-	EL50		> 1000 mg/l	48 h	Tetrahymena		Fresh water	QSAR
organisms					pyriformis			

white mineral oil (petroleum)

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	> 100 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	LC50	OECD 202	> 100 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	NOEL	OECD 201	≥ 100 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Weight of evidence; Growth rate
Long-term toxicity fish	NOEL		≥ 1000 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOEL	Equivalent to OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Read-across; GLP

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2. Persistence and degradability

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	80 %; GLP	28 day(s)	Read-across

Biodegradation soil

Method Value [Duration	Value determination
Equivalent or similar to OECD 304A	59.7 % - 62.6 %; Oxygen	61 day(s)	Read-across
	consumption		

white mineral oil (petroleum)

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F: Manometric Respirometry Test	31 %; GLP	28 day(s)	Read-across

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	0.1 day(s) - 0.6 day(s)	1500000 /cm³	Calculated value
n: 1 1.: 11			

Biodegradation soil

	Method	Value	Duration	Value determination
Ī				Data waiving

Conclusion

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23 Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 8 / 13

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

BIKE7 E-CARE

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

white mineral oil (petroleum)

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
					Data waiving

Log Kow

Method	Remark	Value	Temperature	Value determination
		> 6		Calculated

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	65.8 %	0 %	22.9 %	9.6 %	1.7 %	Calculated value

white mineral oil (petroleum)

(log) Koc

Parameter	Method	Value	Value determination
			Data waiving

Conclusion

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6. Other adverse effects

BIKE7 E-CARE

Fluorinated greenhouse gases (Regulation (EU) No 517/2014)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

white mineral oil (petroleum)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 29* (separately collected fractions (except 15 01): detergents containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23
Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 9 / 13

SECTION 14: Transport information

d (ADR) I.1. UN number	
UN number	1950
1.2. UN proper shipping name	_
Proper shipping name	Aerosols
1.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
1.4. Packing group	
Packing group	
Labels	2.1
1.5. Environmental hazards	
Environmentally hazardous substance mark	no
1.6. Special precautions for user	T
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)
(RID)	
I.1. UN number	1050
UN number	1950
1.2. UN proper shipping name	Agreed
Proper shipping name	Aerosols
I.3. Transport hazard class(es) Hazard identification number	23
	2
Class Classification code	
	jor .
I.4. Packing group Packing group	
Labels	2.1
1.5. Environmental hazards	2.1
Environmentally hazardous substance mark	no
1.6. Special precautions for user	lio
Special previsions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass)
nd waterways (ADN)	induids. To puesage shall not weight more than 50 kg. (g. 655 mass)
I.1. UN number	
UN number	1950
1.2. UN proper shipping name	
Proper shipping name	Aerosols
1.3. Transport hazard class(es)	
Class	2
Classification code	5F
1.4. Packing group	
Packing group	
Labels	2.1
1.5. Environmental hazards	
Environmentally hazardous substance mark	no
1.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
	023
Special provisions	
Special provisions Special provisions	Combination packagings: not more than 1 liter per inner packaging fo
Special provisions Special provisions Limited quantities	Combination packagings: not more than 1 liter per inner packaging for

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23
Date of revision: 2019-05-06

 Revision number: 0503
 Product number: 45574
 10 / 13

Proper shipping name	aerosols
4.3. Transport hazard class(es)	
Class	2.1
4.4. Packing group	
Packing group	
Labels	2.1
4.5. Environmental hazards	
Marine pollutant	-
Environmentally hazardous substance mark	no
4.6. Special precautions for user	·
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging liquids. A package shall not weigh more than 30 kg. (gross mass)
4.7. Transport in bulk according to Annex II of Marpol and the IB	
Annex II of MARPOL 73/78	Not applicable
ICAO TI/IATA DCD)	
(ICAO-TI/IATA-DGR)	
4. <u>1. UN number</u>	l
4.1. UN number UN number	1950
4.1. UN number UN number 4.2. UN proper shipping name	-
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name	1950 Aerosols, flammable
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es)	Aerosols, flammable
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class	-
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group	Aerosols, flammable
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group	Aerosols, flammable 2.1
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels	Aerosols, flammable
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards	Aerosols, flammable 2.1 2.1
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark	Aerosols, flammable 2.1
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user	Aerosols, flammable 2.1 2.1 no
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions	Aerosols, flammable 2.1 2.1 no A145
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions Special provisions	Aerosols, flammable
4.1. UN number UN number 4.2. UN proper shipping name Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions	Aerosols, flammable 2.1 2.1 no A145

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **European legislation:**

VOC content Directive 2010/75/EU

VOC content	Remark
84 %	
532.862 g/l	

Ingredients according to Regulation (EC) No 648/2004 and amendments

≥30% aliphatic hydrocarbons, <5% anionic surfactants

European drinking water standards (Directive 98/83/EC)

white mineral oil (petroleum)

Parameter	Parametric value	Note	Reference
Pesticides	0.1 μg/l		Listed in Annex I, Part B, of Directive 98/83/EC on the quality of water intended for human consumption.
Pesticides — Total	0.5 μg/l		Listed in Annex I, Part B, of Directive 98/83/EC on the quality of water intended for human consumption.

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
· hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics		Shall not be used in: ornamental articles intended to produce light or colour effects by means of different
· white mineral oil (petroleum)	, ,	phases, for example in ornamental lamps and ashtrays,
	(EC) No 1272/2008:	— tricks and jokes,
	(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8	— games for one or more participants, or any article intended to be used as such, even

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23 Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 11 / 13

types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A

(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10:

(c) hazard class 4.1; (d) hazard class 5.1. gories with ornamental aspects,

- 2. Articles not complying with paragraph 1 shall not be placed on the market.
- 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
- can be used as fuel in decorative oil lamps for supply to the general public, and,
- present an aspiration hazard and are labelled with H304,
- 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
- 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil or even sucking the wick of lamps may lead to life- threatening lung damage";

 b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";

c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.

6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled H304, intended for supply to the general public.

7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'

National legislation Belgium

BIKE7 E-CARE

No data available

National legislation The Netherlands

BIKE7 E-CARE

Waterbezwaarlijkheid Z (2); Algemene Beoordelingsmethodiek (ABM)

National legislation France

BIKE7 E-CARE

No data available

National legislation Germany

BIKE7 E-CARE

WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017	
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
TA-Luft	5.2.5	
white mineral oil (petroleum)		
TA-Luft	5.2.5/I	

National legislation United Kingdom

BIKE7 E-CARE

No data available

Other relevant data

BIKE7 E-CARE

No data available

white mineral oil (petroleum)

TLV - Carcinogen Mineral oil, pure, highly and severely refined; A4

15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

SECTION 16: Other information

Full text of any H-statements referred to under heading 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

(*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23
Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 12 / 13

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 3.2; 5; 15 Publication date: 2007-10-23

Date of revision: 2019-05-06

Revision number: 0503 Product number: 45574 13 / 13