

SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

BIKE7 LUBRICATE WET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : BIKE7 LUBRICATE WET
Registration number REACH : Not applicable (mixture)
Product type REACH : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Lubricant

1.2.2 Uses advised against

No uses advised against known

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

BIKE 7*
Industrielaan 5B
B-2250 Olen
☎ +32 14 23 72 03
☎ +32 14 85 97 38
info@bike7.be
*BIKE 7 is a registered trademark of Novatech International N.V.

Manufacturer of the product

Novatech International N.V.
Industrielaan 5B
B-2250 Olen
☎ +32 14 85 97 37
☎ +32 14 85 97 38
info@novatech.be

1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :
+32 14 58 45 45 (BIG)
Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2166 (Public 8 am- 10 pm)
Ireland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2566 (Professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

2.2. Label elements



Signal word

Danger

H-statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.

P-statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)
Technische Schoolstraat 43 A, B-2440 Geel
<http://www.big.be>
© BIG vzw

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Revision number: 0800 (supersedes revision 0700 of 2024-12-29)

Publication date: 2007-07-31

Date of revision: 2026-06-02

BIG number: 45278

1 / 30

878-17438-092-en

BIKE7 LUBRICATE WET

P251	Do not pierce or burn, even after use.
P280	Wear protective gloves, protective clothing and eye protection/face protection.
P264	Wash hands thoroughly after handling.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulation.
Supplemental information	
EUH208	Contains: methyl methacrylate. May produce an allergic reaction.

2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard
Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
butane 01-2119474691-32	106-97-8 203-448-7	C≤40%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 01-2119475515-33	927-510-4	C≤6%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)	Constituent	
hydrocarbons, C6, isoalkanes, < 5% n- hexane 01-2119484651-34	931-254-9	C≤5%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)	Constituent	
distillates (petroleum), hydrotreated light paraffinic 01-2119487077-29	64742-55-8 265-158-7	C≤4%	Asp. Tox. 1; H304	(1)(2)(10)(6)	Constituent	
Distillates (petroleum), solvent-dewaxed heavy paraffinic 01-2119471299-27	64742-65-0 265-169-7	C≤4%	Asp. Tox. 1; H304	(1)(2)(6)(10)	Constituent	
Distillates (petroleum), hydrotreated heavy paraffinic 01-2119484627-25	64742-54-7 265-157-1	C≤4%	Asp. Tox. 1; H304	(1)(2)(6)(10)	Constituent	
Distillates (petroleum), solvent-dewaxed light paraffinic 01-2119480132-48	64742-56-9 265-159-2	C≤4%	Asp. Tox. 1; H304	(1)(2)(10)(6)	Constituent	
n-hexane 01-2119480412-44	110-54-3 203-777-6	C≤0.3%	Flam. Liq. 2; H225 Repr. 2; H361f STOT RE 1; H372 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)(4)	Constituent	
methyl methacrylate 01-2119452498-28	80-62-6 201-297-1	C≤0.2%	Flam. Liq. 2; H225 Skin Sens. 1; H317 Skin Irrit. 2; H315 STOT SE 3; H335	(1)(2)(10)	Constituent	

- (1) For H- and EUH-statements in full: see section 16
(2) Substance with a Community workplace exposure limit
(4) Enumerated in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No. 1907/2006)
(6) Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data
(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006
(21) 1,3-butadiene <0.1%

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

2 / 30

BIKE7 LUBRICATE WET

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

No effects known.

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Take account of environmentally hazardous firefighting water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN ISO 16321). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN ISO 16321). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

BIKE7 LUBRICATE WET

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe strict hygiene.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Protect against frost. Keep out of direct sunlight.

7.2.2 Keep away from:

Heat sources, ignition sources.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

EU

Methyl methacrylate	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	100 ppm
n-Hexane	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	72 mg/m ³

Belgium

Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m ³
Huiles minérales (brouillards)	Time-weighted average exposure limit 8 h	5 mg/m ³
	Short time value	10 mg/m ³
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm
Méthacrylate de méthyle	Time-weighted average exposure limit 8 h	50 ppm
	Time-weighted average exposure limit 8 h	208 mg/m ³
	Short time value	100 ppm
	Short time value	416 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	72 mg/m ³

The Netherlands

Methylmethacrylaat	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	50 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	205 mg/m ³
	Short time value (Public occupational exposure limit value)	100 ppm
	Short time value (Public occupational exposure limit value)	410 mg/m ³
n-Hexaan	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	72 mg/m ³
	Short time value (Public occupational exposure limit value)	40 ppm
	Short time value (Public occupational exposure limit value)	144 mg/m ³
Olienevel (minerale olie)	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	5 mg/m ³

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

4 / 30

BIKE7 LUBRICATE WET

France

Hexane (autres isomères)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	500 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1800 mg/m ³
Hydrocarbures en C6-C12 (ensemble des)	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1000 mg/m ³ (1)
	Short time value (VL: Valeur non réglementaire indicative)	1500 mg/m ³ (1)
	<i>Les valeurs spécifiques fixées pour les hydrocarbures nommément désignés dans la liste restent valable simultanément. Une valeur d'objectif de 500 mg/m³ avait été prévue par la circulaire du 12 juillet 1993, elle devait être réexaminée en 1995 mais ne l'a pas été.</i>	
Méthacrylate de méthyle	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	50 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	205 mg/m ³
	Short time value (VRC: Valeur réglementaire contraignante)	100 ppm
	Short time value (VRC: Valeur réglementaire contraignante)	410 mg/m ³
n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	72 mg/m ³

(1) vapeurs

Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³ (1)
Hexan Isomere (außer n-Hexan) und Methylcyclopentan	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³ (2)
	Time-weighted average exposure limit 8 h (TRGS 900)	500 ppm (2)
Kohlenwasserstoffgemische, Verwendung als Lösemittel (Lösemittelkohlenwasserstoffe), additiv-frei: C6-C8 Aliphaten	Time-weighted average exposure limit 8 h (TRGS 900)	700 mg/m ³ (3)
Methyl-methacrylat	Time-weighted average exposure limit 8 h (TRGS 900)	210 mg/m ³ (4)
	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm (4)
n-Hexan	Time-weighted average exposure limit 8 h (TRGS 900)	180 mg/m ³ (5)
	Time-weighted average exposure limit 8 h (TRGS 900)	50 ppm (5)
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm (1)
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³ (1)

(1) UF: 4 (II)

(2) UF: 2 (II)

(3) Vgl. Nummer 2.9 Anwendung und Geltungsbereich der Arbeitsplatzgrenzwerte für Kohlenwasserstoffgemische; UF: 2 (II)

(4) UF: 2 (I)

(5) UF: 8 (II)

BIKE7 LUBRICATE WET

Austria

Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m ³
Kühlschmierstoffe: Mineralölnebel (unlegierter Kühlschmierstoff)	Tagesmittelwert	5 mg/m ³ (1)
Methylmethacrylat	Tagesmittelwert (MAK)	50 ppm
	Tagesmittelwert (MAK)	210 mg/m ³
	Kurzzeitwert 5(Mow) 8x (MAK)	100 ppm
	Kurzzeitwert 5(Mow) 8x (MAK)	420 mg/m ³
n-Hexan	Tagesmittelwert (MAK)	20 ppm
	Tagesmittelwert (MAK)	72 mg/m ³
	Kurzzeitwert 15(Miw) 4x (MAK)	80 ppm
	Kurzzeitwert 15(Miw) 4x (MAK)	288 mg/m ³
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m ³
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m ³

(1) Einatembare Fraktion

UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m ³
Methyl methacrylate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	50 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	208 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	100 ppm
	Short time value (Workplace exposure limit (EH40/2005))	416 mg/m ³
n-Hexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	20 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	72 mg/m ³

Ireland

Aliphatic hydrocarbon gases Alkanes (C1-C3): Propane	<i>Asphx.</i>	
Butane, all isomers	Short time value (Advisory occupational exposure limit values)	1000 ppm
Methyl methacrylate	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	50 ppm
	Short time value (Binding occupational exposure limit values)	100 ppm
n-Hexane	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	20 ppm
	Time-weighted average exposure limit 8 h (Binding occupational exposure limit values)	72 mg/m ³

USA (TLV-ACGIH)

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
	<i>Explosion hazard</i>	
Hexane (Commercial,	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	100 ppm
Methyl methacrylate	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
	Short time value (TLV - Adopted Value)	100 ppm
Mineral oil, excluding metal working fluids: Poorly and mildly refined	<i>Exposure by all routes should be carefully controlled to levels as low as possible</i>	
Mineral oil, excluding metal working fluids: Pure, highly and severely refined	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	5 mg/m ³ (1)
n-Hexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm
Propane	<i>See Appendix F: Minimal Oxygen Content; Simple asphyxiant, Explosion hazard</i>	

(1) (I): Inhalable fraction

b) National biological limit values

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

6 / 30

BIKE7 LUBRICATE WET

If limit values are applicable and available these will be listed below.

Germany

Hexan (n-Hexan) (2,5-Hexandion plus 4,5-Dihydroxy-2-Hexanon (nach Hydrolyse))	Urin: expositionsende, bzw. schichtende	5 mg/l	
---	---	--------	--

USA (BEI-ACGIH)

n-Hexane (2,5-Hexanedione)	Urine: end of shift	0,5 mg/L	Without hydrolysis
----------------------------	---------------------	----------	--------------------

8.1.2 Sampling methods

Product name	Test	Number
Methyl ester of methacrylic acid	NIOSH	2537
Methyl Methacrylate	NIOSH	2537
Methyl Methacrylate	NIOSH	3900
Methyl Methacrylate	OSHA	94
Methyl Methacrylate	SKC NON	54
n-Hexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
n-Hexane (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
n-Hexane (Volatile Organic compounds)	NIOSH	2549
n-Hexane	NIOSH	3900
n-Hexane	OSHA	5000
Oil Mist (Mineral)	NIOSH	5026

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 Threshold values

DNEL/DMEL - Workers

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2085 mg/m ³	
	Long-term systemic effects dermal	300 mg/kg bw/day	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	5306 mg/m ³	
	Long-term systemic effects dermal	13964 mg/kg bw/day	

distillates (petroleum), hydrotreated light paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.73 mg/m ³	
	Long-term local effects inhalation	5.58 mg/m ³	
	Long-term systemic effects dermal	0.97 mg/kg bw/day	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.73 mg/m ³	
	Long-term local effects inhalation	5.58 mg/m ³	
	Long-term systemic effects dermal	0.97 mg/kg bw/day	

Distillates (petroleum), hydrotreated heavy paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.73 mg/m ³	
	Long-term local effects inhalation	5.58 mg/m ³	
	Long-term systemic effects dermal	0.97 mg/kg bw/day	

Distillates (petroleum), solvent-dewaxed light paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	2.73 mg/m ³	
	Long-term local effects inhalation	5.58 mg/m ³	
	Long-term systemic effects dermal	0.97 mg/kg bw/day	

n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	75 mg/m ³	
	Long-term systemic effects dermal	11 mg/kg bw/day	

methyl methacrylate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	348.4 mg/m ³	
	Long-term local effects inhalation	208 mg/m ³	
	Acute local effects inhalation	416 mg/m ³	
	Long-term systemic effects dermal	13.67 mg/kg bw/day	
	Long-term local effects dermal	1.5 mg/cm ²	
	Acute local effects dermal	1.5 mg/cm ²	

DNEL/DMEL - General population

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

7 / 30

BIKE7 LUBRICATE WET

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	447 mg/m ³	
	Long-term systemic effects dermal	149 mg/kg bw/day	
	Long-term systemic effects oral	149 mg/kg bw/day	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	1131 mg/m ³	
	Long-term systemic effects dermal	1377 mg/kg bw/day	
	Long-term systemic effects oral	1301 mg/kg bw/day	

distillates (petroleum), hydrotreated light paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects oral	19 mg/kg bw/day	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects oral	0.74 mg/kg bw/day	

Distillates (petroleum), hydrotreated heavy paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects oral	0.74 mg/kg bw/day	

Distillates (petroleum), solvent-dewaxed light paraffinic

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects oral	0.74 mg/kg bw/day	

n-hexane

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	16 mg/m ³	
	Long-term systemic effects dermal	5.3 mg/kg bw/day	
	Long-term systemic effects oral	4 mg/kg bw/day	

methyl methacrylate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Long-term systemic effects inhalation	74.3 mg/m ³	
	Long-term local effects inhalation	104 mg/m ³	
	Acute local effects inhalation	208 mg/m ³	
	Long-term systemic effects dermal	8.2 mg/kg bw/day	
	Long-term local effects dermal	1.5 mg/cm ²	
	Acute local effects dermal	1.5 mg/cm ²	
	Long-term systemic effects oral	8.2 mg/kg bw/day	

PNEC

distillates (petroleum), hydrotreated light paraffinic

Compartments	Value	Remark
Oral	9.33 mg/kg food	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Compartments	Value	Remark
Oral	9.33 mg/kg food	

Distillates (petroleum), hydrotreated heavy paraffinic

Compartments	Value	Remark
Oral	9.33 mg/kg food	

Distillates (petroleum), solvent-dewaxed light paraffinic

Compartments	Value	Remark
Oral	9.33 mg/kg food	

methyl methacrylate

Compartments	Value	Remark
Fresh water	0.94 mg/l	
Marine water	0.094 mg/l	
Fresh water (intermittent releases)	0.69 mg/l	
STP	10 mg/l	
Fresh water sediment	10.2 mg/kg sediment dw	
Marine water sediment	1.02 mg/kg sediment dw	
Soil	1.48 mg/kg soil dw	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe strict hygiene. Do not eat, drink or smoke during work.

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

8 / 30

BIKE7 LUBRICATE WET

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

c) Eye protection:

Protective goggles (EN ISO 16321).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Colour	Yellow
Odour	Characteristic odour
Odour threshold	No data available in the literature
Melting point	Not applicable (aerosol)
Boiling point	60 °C - 300 °C ; Liquid
Flammability	Extremely flammable aerosol.
Explosion limits	1.1 - 7.4 vol % ; Propellant
Flash point	Not applicable (aerosol)
Auto-ignition temperature	Not applicable (aerosol)
Decomposition temperature	No data available in the literature
pH	Not applicable (non-soluble in water)
Kinematic viscosity	1 mm ² /s ; 20 °C ; Liquid
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid
Solubility	Water ; insoluble
Log Kow	Not applicable (mixture)
Vapour pressure	8530 hPa ; 20 °C ; Propellant
Absolute density	840 kg/m ³ ; 20 °C
Relative density	0.84 ; 20 °C
Relative vapour density	> 1
Particle size	Not applicable (aerosol)

9.2. Other information

Evaporation rate	7 ; Butyl acetate
------------------	-------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO₂ are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

BIKE7 LUBRICATE WET

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

9 / 30

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 5840 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50		2800 mg/kg bw - 3100 mg/kg bw	24 h	Rat (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 23.3 mg/l air	4 h	Rat (male / female)	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	> 16750 mg/kg bw		Rat (male)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	259.35 mg/l	4 h	Rat (male)	Read-across	

distillates (petroleum), hydrotreated light paraffinic

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	OECD 403	> 5.53 mg/l air	4 h	Rat (male / female)	Read-across	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	OECD 403	> 5.53 mg/l air	4 h	Rat (male / female)	Read-across	

Distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	OECD 403	> 5.53 mg/l air	4 h	Rat (male / female)	Read-across	

Distillates (petroleum), solvent-dewaxed light paraffinic

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	OECD 401	> 5000 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50	OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	LC50	OECD 403	> 5.53 mg/l air	4 h	Rat (male / female)	Read-across	

n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	16000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 17.6 mg/l air	24 h	Rat (male)	Experimental value	

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

10 / 30

BIKE7 LUBRICATE WET

methyl methacrylate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		9400 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 5000 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (vapours)	LC50		29.8 mg/l air	4 h	Rat (male / female)	Experimental value	

Conclusion

Not classified for acute toxicity

Corrosion/irritation

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	EPA OPPTS 870.2400		1; 24; 48; 72 hrs; 7 days	Rabbit	Read-across	Single treatment without rinsing
Skin	Irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	
Skin	Irritating; category 2					Literature study	

distillates (petroleum), hydrotreated light paraffinic

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Slightly irritating	Equivalent to OECD 404	24 h	24; 48; 72 hours	Rabbit	Read-across	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	OECD 404	24 h	24; 48; 72 hours	Rabbit	Read-across	

Distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Slightly irritating		24 h	24; 48; 72 hours	Rabbit	Read-across	

Distillates (petroleum), solvent-dewaxed light paraffinic

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Not irritating	Equivalent to OECD 404	24 h	24; 48; 72 hours	Rabbit	Read-across	

n-hexane

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405		24; 48; 72 hours	Rabbit	Read-across	Single treatment
Skin	Irritating	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Read-across	

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

11 / 30

BIKE7 LUBRICATE WET

methyl methacrylate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Draize Test		24; 48; 72 hours	Rabbit	Experimental value	Single treatment without rinsing
Skin	Irritating		4 h	24; 72 hours	Rabbit	Experimental value	
Inhalation (vapours)	Irritating; STOT SE cat.3					Annex VI	

Conclusion

Causes skin irritation.
Not classified as irritating to the eyes
Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

BIKE7 LUBRICATE WET

No (test)data on the mixture available
Judgement is based on the relevant ingredients
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male / female)	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Not sensitizing	Equivalent to OECD 429			Mouse (male / female)	Read-across	

distillates (petroleum), hydrotreated light paraffinic

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		48 hours	Guinea pig (male)	Read-across	
Skin	Not sensitizing	Human observation			Human (male / female)	Experimental value	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male)	Read-across	
Skin	Not sensitizing	Human observation			Human (male / female)	Experimental value	

Distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male)	Read-across	

Distillates (petroleum), solvent-dewaxed light paraffinic

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406			Guinea pig (male)	Read-across	

n-hexane

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Not sensitizing	Equivalent to OECD 429			Mouse	Experimental value	

methyl methacrylate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Dermal (on the ears)	Sensitizing	Equivalent to OECD 429			Mouse	Experimental value	
	Not sensitizing					Experimental value	

Conclusion

Not classified as sensitizing for inhalation
Not classified as sensitizing for skin

Specific target organ toxicity

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

12 / 30

BIKE7 LUBRICATE WET

Judgement is based on the relevant ingredients
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOAEC	Subchronic toxicity test	12470 mg/m ³ air	Central nervous system (no effect)	16 weeks (daily)	Rat (male)	Read-across	
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	12350 mg/m ³ air	No adverse systemic effects	26 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation (vapours)	LOAEL	Equivalent to OECD 413	1650 mg/m ³ air	Central nervous system (cns depression)	26 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral							Data waiving	
Dermal							Data waiving	
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	10504 mg/m ³ air	No effect	13 weeks (6h / day, 5 days / week)	Rat (male)	Read-across	
Inhalation			STOT SE cat.3	Drowsiness, dizziness			Literature study	

distillates (petroleum), hydrotreated light paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Dermal	NOAEL	OECD 410	1000 mg/kg bw/day	No adverse systemic effects	4 weeks (6h / day, 3 days / week)	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	NOAEC	Equivalent to OECD 412	> 980 mg/m ³ air	No adverse systemic effects	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	LOAEL	Equivalent to OECD 408	125 mg/kg bw/day	Overall effects	13 weeks (5 days / week)	Rat (male)	Read-across	
Dermal	NOAEL	OECD 410	1000 mg/kg bw/day	No effect	28 weeks (6h / day, 3 days / week)	Rabbit (male / female)	Read-across	
Inhalation	NOAEC	Equivalent to OECD 412	> 960 mg/l	No effect	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

Distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	LOAEL	Equivalent to OECD 408	125 mg/kg bw/day	Overall effects	13 weeks (5 days / week)	Rat (male)	Read-across	
Dermal	NOAEL systemic effects	OECD 410	1000 mg/kg bw/day	No adverse systemic effects	4 weeks (6h / day, 3 days / week)	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	NOEC	Equivalent to OECD 412	220 mg/m ³ air	Lungs (no effect)	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	
Inhalation (aerosol)	NOAEC systemic effects	Equivalent to OECD 412	> 980 mg/m ³ air	No adverse systemic effects	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

BIKE7 LUBRICATE WET

Distillates (petroleum), solvent-dewaxed light paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	LOAEL	Equivalent to OECD 408	125 mg/kg bw/day	Overall effects	13 weeks (5 days / week)	Rat (male)	Read-across	
Dermal	NOAEL	OECD 410	1000 mg/kg bw/day	No adverse systemic effects	4 weeks (6h / day, 3 days / week)	Rabbit (male / female)	Read-across	
Inhalation (aerosol)	NOAEC	Equivalent to OECD 412	> 980 mg/m ³ air	No adverse systemic effects	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	
Inhalation (aerosol)	NOEC	Equivalent to OECD 412	220 mg/m ³ air	Lungs (no effect)	4 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

n-hexane

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (stomach tube)	NOAEL	OECD 408	40 mg/kg bw/day	No effect	13 weeks (daily)	Rat (male / female)	Experimental value	
Oral (stomach tube)	LOAEL	OECD 408	200 mg/kg bw/day	Liver; kidney (weight gain)	13 weeks (daily)	Rat (male / female)	Experimental value	
Inhalation (vapours)	LOAEC	Subchronic toxicity test	3000 ppm	Central nervous system (neurotoxic effects)	16 weeks (daily)	Rat (male)	Experimental value	
Inhalation (vapours)			STOT SE cat.3	Drowsiness, dizziness			Annex VI	

methyl methacrylate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Oral (drinking water)	NOAEL		≥ 124.1 mg/kg bw/day	No effect	104 week(s)	Rat (male)	Experimental value	
Oral (drinking water)	NOAEL		≥ 164 mg/kg bw/day	No effect	104 week(s)	Rat (female)	Experimental value	
Inhalation (vapours)	NOAEC systemic effects	Equivalent to OECD 453	1640 mg/m ³ air	No adverse systemic effects	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Inhalation (vapours)	NOAEC local effects	Equivalent to OECD 453	104 mg/m ³ air	Nose (no effect)	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

Conclusion

Not classified for subchronic toxicity

Mutagenicity (in vitro)

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Rat liver cells	No effect	Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S. typhimurium)	No effect	Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Read-across	

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

14 / 30

BIKE7 LUBRICATE WET

distillates (petroleum), hydrotreated light paraffinic

Result	Method	Test substrate	Effect	Value determination	Remark
Positive with metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	Mutagenic	Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Read-across	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result	Method	Test substrate	Effect	Value determination	Remark
Positive with metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Read-across	

Distillates (petroleum), hydrotreated heavy paraffinic

Result	Method	Test substrate	Effect	Value determination	Remark
Positive with metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)	No effect	Read-across	

Distillates (petroleum), solvent-dewaxed light paraffinic

Result	Method	Test substrate	Effect	Value determination	Remark
Positive with metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Read-across	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 473	Chinese hamster ovary (CHO)		Read-across	
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)		Read-across	

n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

methyl methacrylate

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	OECD 471	Bacteria (S. typhimurium and E. coli)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	OECD 476	Chinese hamster lung fibroblasts (V79)	No effect	Experimental value	

Mutagenicity (in vivo)

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Inhalation (vapours))	Equivalent to OECD 478	8 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Inhalation (vapours))	Equivalent to OECD 475	5 days (6h / day)	Rat (male / female)	Bone marrow	Read-across	

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

15 / 30

BIKE7 LUBRICATE WET

distillates (petroleum), hydrotreated light paraffinic

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow (no effect)	Read-across	Single intraperitoneal injection

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow (no effect)	Read-across	Single intraperitoneal injection

Distillates (petroleum), hydrotreated heavy paraffinic

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow (no effect)	Read-across	Single intraperitoneal injection

Distillates (petroleum), solvent-dewaxed light paraffinic

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Intraperitoneal)	OECD 474		Mouse (male / female)	Bone marrow (no effect)	Read-across	Single intraperitoneal injection

n-hexane

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Oral (stomach tube))	OECD 475	13 weeks (daily)	Rat (male / female)	No effect	Experimental value	

methyl methacrylate

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Negative (Inhalation (vapours))	Equivalent to OECD 478	5 days (6h / day)	Mouse (male)	No effect	Experimental value	

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Unknown				No carcinogenic effect			Weight of evidence	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	31743 mg/m ³	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	

distillates (petroleum), hydrotreated light paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Dermal	Dose level	Equivalent to OECD 451	0.2 ml - 0.25 ml	No carcinogenic effect	78 week(s)	Mouse (female)	Read-across	

Distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Dermal		Equivalent to OECD 451		No carcinogenic effect	78 week(s)	Mouse (female)	Read-across	

n-hexane

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	3000 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Mouse (female)	Experimental value	
Inhalation (vapours)	LOAEC	Equivalent to OECD 451	9018 ppm	Liver (tumor formation)	104 weeks (6h / day, 5 days / week)	Mouse (female)	Experimental value	
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9018 ppm	No carcinogenic effect	104 weeks (6h / day, 5 days / week)	Mouse (male)	Experimental value	

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

16 / 30

BIKE7 LUBRICATE WET

methyl methacrylate

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	≥ 2.05 mg/l air	No carcinogenic effect	102 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	≥ 124 mg/kg bw/day	No carcinogenic effect	104 weeks (daily)	Rat (male)	Experimental value	
Oral (drinking water)	NOAEL	Carcinogenic toxicity study	≥ 162 mg/kg bw/day	No carcinogenic effect	104 weeks (daily)	Rat (female)	Experimental value	

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	1200 ppm	10 days (gestation, 6h / day)	Rat (female)	No effect	Read-across	
Maternal toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	1200 ppm	10 days (gestation, 6h / day)	Rat	No effect	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	31680 mg/m ³	10 days (gestation, 6h / day)	Rat	No effect	Read-across	
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	10560 mg/m ³	10 days (gestation, 6h / day)	Rat	No effect	Read-across	
Effects on fertility (Inhalation (vapours))	NOEC	Equivalent to OECD 416	≥ 31680 mg/m ³		Rat (male / female)	No effect	Read-across	

distillates (petroleum), hydrotreated light paraffinic

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Dermal)	NOAEL	Equivalent to OECD 414	2000 mg/kg bw/day	20 days (gestation, daily)	Rat (female)	No effect	Read-across	
Maternal toxicity (Dermal)	LOAEL	Equivalent to OECD 414	125 mg/kg bw/day	20 days (gestation, daily)	Rat (female)	Irritation	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 421	≥ 1000 mg/kg bw/day		Rat (male / female)	No effect	Read-across	

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Dermal)	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	20 days (gestation, daily)	Rat	No effect	Read-across	
Developmental toxicity (Dermal)	LOAEL	Equivalent to OECD 414	125 mg/kg bw/day	20 days (gestation, daily)	Rat	Embryotoxicity and fetotoxicity	Read-across	
Maternal toxicity (Dermal)	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	20 days (gestation, daily)	Rat	No effect	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 421	≥ 1000 mg/kg bw/day		Rat (male / female)	No effect	Read-across	

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

17 / 30

BIKE7 LUBRICATE WET

Distillates (petroleum), hydrotreated heavy paraffinic

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Dermal)	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	20 days (gestation, daily)	Rat	No effect	Read-across	
Maternal toxicity (Dermal)	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	20 days (gestation, daily)	Rat	No effect	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 421	≥ 1000 mg/kg bw/day		Rat (male / female)	No effect	Read-across	

Distillates (petroleum), solvent-dewaxed light paraffinic

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Dermal)	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	20 days (gestation, daily)	Rat	No effect	Read-across	
Developmental toxicity (Dermal)	LOAEL	Equivalent to OECD 414	125 mg/kg bw/day	20 days (gestation, daily)	Rat	Embryotoxicity and fetotoxicity	Read-across	
Maternal toxicity (Dermal)	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	20 days (gestation, daily)	Rat	No effect	Read-across	
Maternal toxicity (Dermal)	LOAEL	Equivalent to OECD 414	125 mg/kg bw/day	20 days (gestation, daily)	Rat	Maternal toxicity	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 421	≥ 1000 mg/kg bw/day		Rat (male / female)	No effect	Read-across	

n-hexane

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	200 ppm	15 days (gestation, daily)	Rat	Foetus (no effect)	Experimental value	
Developmental toxicity (Inhalation (vapours))	LOAEC	Developmental toxicity study	1000 ppm	15 days (gestation, daily)	Rat	Foetus (reduced fetal bodyweights)	Experimental value	
Maternal toxicity (Inhalation (vapours))	NOAEC	Developmental toxicity study	200 ppm	15 days (gestation, daily)	Rat	No effect	Experimental value	
Maternal toxicity (Inhalation (vapours))	LOAEC	Developmental toxicity study	1000 ppm	15 days (gestation, daily)	Rat	Weight reduction	Experimental value	
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm	≥ 13 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect	Experimental value	
Effects on fertility			category 2			Adverse effects on fertility	Annex VI	

methyl methacrylate

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Inhalation (vapours))	NOAEC	OECD 414	8.44 mg/l air	10 days (6h / day)	Rat	Foetus (no effect)	Experimental value	
Maternal toxicity (Inhalation (vapours))	NOAEC	OECD 414	8.44 mg/l air	10 days (6h / day)	Rat	No effect	Experimental value	
Effects on fertility (Oral (stomach tube))	NOAEL	OECD 416	400 mg/kg bw/day		Rat (male / female)	No effect	Experimental value	

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

BIKE7 LUBRICATE WET

Judgement is based on the relevant ingredients

Not classified for aspiration toxicity

Toxicity other effects

BIKE7 LUBRICATE WET

No (test)data on the mixture available

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Inhalation	NOAEC	Equivalent to OECD 424	9000 ppm	Central nervous system (overall effects)	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Experimental value	

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

18 / 30

BIKE7 LUBRICATE WET

Chronic effects from short and long-term exposure

BIKE7 LUBRICATE WET

Skin rash/inflammation.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

BIKE7 LUBRICATE WET

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 13 mg/l WAF	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	4.6 mg/l WAF - 10 mg/l WAF	48 h	Daphnia magna	Static system	Fresh water	Read-across; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	29 mg/l WAF	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; GLP
	NOELR	OECD 201	6.3 mg/l WAF	72 h	Raphidocelis subcapitata	Static system	Fresh water	Read-across; GLP
Long-term toxicity fish	EL10		1.4 mg/l	60 day(s)	Oncorhynchus mykiss			QSAR; Estimated value
Long-term toxicity aquatic crustacea	NOEC	OECD 211	0.17 mg/l WAF	21 day(s)	Daphnia magna	Static system	Fresh water	Read-across; GLP
Toxicity aquatic micro-organisms	EL50		> 1000 mg/l	15 h	Activated sludge		Fresh water	QSAR; Estimated value

Classification of this substance is debatable as it does not correspond to the conclusion from the test

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	12 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Read-across; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	3 mg/l	48 h	Daphnia magna	Static system		Read-across; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	55 mg/l	72 h	Raphidocelis subcapitata	Static system		Read-across; Growth rate
	NOEL	OECD 201	30 mg/l	72 h	Raphidocelis subcapitata	Static system		Read-across; Growth rate
Long-term toxicity fish	EL10	Petrotox computer model	3.3 mg/l	60 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Estimated value
Long-term toxicity aquatic crustacea	EL10	Petrotox computer model	5.8 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR; Estimated value
Toxicity aquatic micro-organisms	EL50		> 1000 mg/l	15 h	Activated sludge		Fresh water	QSAR; Estimated value

distillates (petroleum), hydrotreated light paraffinic

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 100 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	Equivalent to OECD 202	> 10000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	NOEL	OECD 201	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		≥ 1000 mg/l	14 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEL	Equivalent to OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

19 / 30

BIKE7 LUBRICATE WET

Distillates (petroleum), solvent-dewaxed heavy paraffinic

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 100 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	Equivalent to OECD 202	> 10000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	NOEL	OECD 201	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		≥ 1000 mg/l	14 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEL	OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

Distillates (petroleum), hydrotreated heavy paraffinic

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 100 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	Equivalent to OECD 202	> 10000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Nominal concentration
Toxicity algae and other aquatic plants	NOEL	OECD 201	≥ 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		≥ 1000 mg/l	14 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEL	OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

Distillates (petroleum), solvent-dewaxed light paraffinic

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 100 mg/l	96 h	Pimephales promelas	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	Equivalent to OECD 202	> 10000 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	NOEL	OECD 201	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOELR		≥ 1000 mg/l	14 day(s)	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Long-term toxicity aquatic crustacea	NOEL	Equivalent to OECD 211	10 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; GLP

n-hexane

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	12 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Estimated value; Lethal
Acute toxicity crustacea	EL50	OECD 202	3 mg/l	48 h	Daphnia magna	Static system	Fresh water	Read-across; Nominal concentration
Toxicity algae and other aquatic plants	EL50		9.3 mg/l	72 h	Pseudokirchneriella subcapitata		Fresh water	Estimated value; Growth rate
	NOELR		2.1 mg/l	72 h	Pseudokirchneriella subcapitata		Fresh water	Estimated value; Growth rate
Long-term toxicity fish	NOELR		2.8 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	Estimated value; Growth rate
Long-term toxicity aquatic crustacea	NOELR		4.9 mg/l	21 day(s)	Daphnia magna		Fresh water	Estimated value; Reproduction
Toxicity aquatic micro-organisms	EL50		48 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth

Classification of this substance is debatable as it does not correspond to the conclusion from the test

BIKE7 LUBRICATE WET

methyl methacrylate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		> 100 mg/l		Pisces			Literature study
Acute toxicity crustacea	EC50	EPA OTS 797.1300	69 mg/l	48 h	Daphnia magna	Flow-through system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	EC50	OECD 201	> 110 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
	NOEC	OECD 201	110 mg/l	72 h	Pseudokirchneriella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	OECD 210	9.4 mg/l	35 day(s)	Danio rerio	Flow-through system	Fresh water	Experimental value; GLP
Long-term toxicity aquatic crustacea	NOEC	OECD 211	37 mg/l	21 day(s)	Daphnia magna	Flow-through system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro-organisms	EC50		> 178 mg/l	48 h	Chilomas sp.			Literature study

Conclusion

Harmful to aquatic life with long lasting effects.

12.2. Persistence and degradability

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Experimental value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Read-across

distillates (petroleum), hydrotreated light paraffinic

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	31 %; Oxygen consumption	28 day(s)	Experimental value

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	31 %; Oxygen consumption	28 day(s)	Experimental value

Distillates (petroleum), hydrotreated heavy paraffinic

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	31 %; Oxygen consumption	28 day(s)	Experimental value

Distillates (petroleum), solvent-dewaxed light paraffinic

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	31 %; Oxygen consumption	28 day(s)	Experimental value

n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; Oxygen consumption	28 day(s)	Read-across

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	23.5 h	1.5E6 /cm ³	Calculated value

methyl methacrylate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301C	94 %; Oxygen consumption	14 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.92	7 h	1.5E6 /cm ³	QSAR

Biodegradation soil

Method	Value	Duration	Value determination
	> 99 %	2 day(s)	Experimental value

Half-life water (t1/2 water)

Method	Value	Primary degradation/mineralisation	Value determination
	53 month(s); pH = 7		Experimental value

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

21 / 30

BIKE7 LUBRICATE WET

Conclusion

Water

Contains non readily biodegradable component(s)

12.3. Bioaccumulative potential

BIKE7 LUBRICATE WET

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN		3.1 - 3.8	20 °C	QSAR

hydrocarbons, C6, isoalkanes, < 5% n-hexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	BCFBAF v3.01	≤ 550 l/kg; Fresh weight		Pisces	QSAR

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		3.6	20 °C	Experimental value

distillates (petroleum), hydrotreated light paraffinic

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available in the literature			

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available in the literature			

Distillates (petroleum), hydrotreated heavy paraffinic

Log Kow

Method	Remark	Value	Temperature	Value determination
KOWWIN	Estimated value	2 - 18		QSAR

Distillates (petroleum), solvent-dewaxed light paraffinic

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available in the literature			

n-hexane

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		4	20 °C	Experimental value

methyl methacrylate

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		1.4	20 °C	Experimental value

Conclusion

Contains bioaccumulative component(s)

12.4. Mobility in soil

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

(log) Koc

Parameter	Method	Value	Value determination
Koc		386 - 1453	QSAR
log Koc		2.6 - 3.2	Calculated value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

(log) Koc

Parameter	Method	Value	Value determination
Koc		≤ 1453	QSAR
log Koc		≤ 3.2	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Mackay level III	94 %	0 %	2.1 %	0.5 %	3.8 %	Calculated value

BIKE7 LUBRICATE WET

distillates (petroleum), hydrotreated light paraffinic

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	5.3 - 5.8	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	0.045 %		60 %	38 %	2.5 %	Calculated value

Distillates (petroleum), solvent-dewaxed heavy paraffinic

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	5.3 - 5.8	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	0.045 %		60 %	38 %	2.5 %	Calculated value

Distillates (petroleum), hydrotreated heavy paraffinic

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	1.7 - 15	QSAR

Distillates (petroleum), solvent-dewaxed light paraffinic

(log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	5.3 - 5.8	Calculated value

Percent distribution

Method	Fraction air	Fraction biota	Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model Level III	0.045 %		60 %	38 %	2.5 %	Calculated value

n-hexane

(log) Koc

Parameter	Method	Value	Value determination
Koc		1453	QSAR
log Koc		3.2	Calculated value

methyl methacrylate

(log) Koc

Parameter	Method	Value	Value determination
log Koc	EPA OTS 796.2750	0.94 - 1.9	Experimental value

Conclusion

Contains component(s) that adsorb(s) into the soil

12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

12.7. Other adverse effects

PMT conclusion

Does not contain component(s) that meet(s) the criteria of PMT and/or vPvM as listed in Annex I of Regulation (EC) No 1272/2008

BIKE7 LUBRICATE WET

Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

BIKE7 LUBRICATE WET

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

distillates (petroleum), hydrotreated light paraffinic

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

Distillates (petroleum), hydrotreated heavy paraffinic

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

Distillates (petroleum), solvent-dewaxed light paraffinic

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

n-hexane

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

methyl methacrylate

Greenhouse gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

Groundwater

Groundwater pollutant

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1. Waste treatment methods

13.1.1 Provisions relating to waste

European Union

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing hazardous substances). Depending on branch of industry and production process, also other waste codes may be applicable.

13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste.

Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

13.1.3 Packaging/Container

European Union

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

BIKE7 LUBRICATE WET

SECTION 14: Transport information

Road (ADR)

14.1. UN number or ID number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Hazard identification number	
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Rail (RID)

14.1. UN number or ID number	UN number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Hazard identification number	23
	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Inland waterways (ADN)

14.1. UN number or ID number	UN number/ID number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Class	2
	Classification code	5F
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).

Sea (IMDG/IMSBC)

14.1. UN number or ID number	UN number	1950
------------------------------	-----------	------

BIKE7 LUBRICATE WET

14.2. UN proper shipping name	Proper shipping name	aerosols
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Marine pollutant	-
	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	190
	Special provisions	277
	Special provisions	327
	Special provisions	344
	Special provisions	381
	Special provisions	63
	Special provisions	959
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg (gross mass).
14.7. Maritime transport in bulk according to IMO instruments	Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1. UN number or ID number	UN number/ID number	1950
14.2. UN proper shipping name	Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	Class	2.1
14.4. Packing group	Packing group	
	Labels	2.1
14.5. Environmental hazards	Environmentally hazardous substance mark	no
14.6. Special precautions for user	Special provisions	A145
	Special provisions	A167
	Special provisions	A802
Passenger and cargo transport	Limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
67.31 %	
447.908 g/l	

Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)	Group	For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability

REACH Candidate list

Contains component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

REACH Annex XIV - Authorisation

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

26 / 30

BIKE7 LUBRICATE WET

· hydrocarbons, C7, n-alkanes, isoalkanes, cyclics · hydrocarbons, C6, isoalkanes, < 5% n-hexane · distillates (petroleum), hydrotreated light paraffinic · Distillates (petroleum), solvent-dewaxed heavy paraffinic · Distillates (petroleum), hydrotreated heavy paraffinic · Distillates (petroleum), solvent-dewaxed light paraffinic · n-hexane · methyl methacrylate	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects, 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304, 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN). 5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: “Keep lamps filled with this liquid out of the reach of children”; and, by 1 December 2010, “Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage”; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: “Just a sip of grill lighter may lead to life threatening lung damage”; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· hydrocarbons, C7, n-alkanes, isoalkanes, cyclics · hydrocarbons, C6, isoalkanes, < 5% n-hexane · n-hexane · methyl methacrylate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: — metallic glitter intended mainly for decoration, — artificial snow and frost, — “whoopie” cushions, — silly string aerosols, — imitation excrement, — horns for parties, — decorative flakes and foams, — artificial cobwebs, — stink bombs. 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: “For professional users only”. 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
· n-hexane · methyl methacrylate	Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2 — serious eye damage category 1 or eye irritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081

National legislation Belgium BIKE7 LUBRICATE WET

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

27 / 30

BIKE7 LUBRICATE WET

No data available

National legislation The Netherlands

BIKE7 LUBRICATE WET

Waterbezwaarlijkheid	Z (1); Algemene Beoordelingsmethodiek (ABM)
<u>distillates (petroleum), hydrotreated light paraffinic</u>	
SZW - Lijst van mutagene stoffen	aardoliegassen en residuen; Opgenomen in SZW-lijst van mutagene stoffen
<u>Distillates (petroleum), solvent-dewaxed heavy paraffinic</u>	
SZW - Lijst van kankerverwekkende stoffen	(complexe) aardolie- en steenkoolderivaten; Opgenomen in SZW-lijst van kankerverwekkende stoffen
SZW - Lijst van mutagene stoffen	aardoliegassen en residuen; Opgenomen in SZW-lijst van mutagene stoffen
<u>Distillates (petroleum), hydrotreated heavy paraffinic</u>	
SZW - Lijst van mutagene stoffen	aardoliegassen en residuen; Opgenomen in SZW-lijst van mutagene stoffen
<u>n-hexane</u>	
SZW - Lijst van voor de voortplanting giftige stoffen (vruchtbaarheid)	n-hexaan; Opgenomen in SZW-lijst van voor de voortplanting giftige stoffen (vruchtbaarheid); 2

National legislation France

BIKE7 LUBRICATE WET

No data available

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Catégorie cancérogène	Hydrocarbures en C6-C12 (ensemble des)
Catégorie mutagène	Hydrocarbures en C6-C12 (ensemble des)
<u>n-hexane</u>	
Catégorie toxique pour la reproduction	n-Hexane; R2

National legislation Germany

BIKE7 LUBRICATE WET

Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017
<u>hydrocarbons, C7, n-alkanes, isoalkanes, cyclics</u>	
TA-Luft	5.2.5
<u>hydrocarbons, C6, isoalkanes, < 5% n-hexane</u>	
TA-Luft	5.2.5/I
<u>distillates (petroleum), hydrotreated light paraffinic</u>	
TA-Luft	5.2.5
<u>Distillates (petroleum), solvent-dewaxed heavy paraffinic</u>	
TA-Luft	5.2.5
<u>Distillates (petroleum), hydrotreated heavy paraffinic</u>	
TA-Luft	5.2.5
<u>Distillates (petroleum), solvent-dewaxed light paraffinic</u>	
TA-Luft	5.2.5
<u>n-hexane</u>	
TA-Luft	5.2.5/I
TRGS900 - Risiko der Fruchtschädigung	n-Hexan; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden
<u>methyl methacrylate</u>	
TA-Luft	5.2.5
TRGS900 - Risiko der Fruchtschädigung	Methyl-methacrylat; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes nicht befürchtet zu werden

National legislation Austria

BIKE7 LUBRICATE WET

No data available

distillates (petroleum), hydrotreated light paraffinic

Krebserzeugend	Mineralöle, die zuvor in Verbrennungsmotoren zur Schmierung und Kühlung der beweglichen Teile des Motors verwendet wurden; III
besondere Gefahr der Hautresorption	Mineralöle, die zuvor in Verbrennungsmotoren zur Schmierung und Kühlung der beweglichen Teile des Motors verwendet wurden; H
<u>n-hexane</u>	
Fortpflanzungsgefährdend [Beeinträchtigung der Fortpflanzungsfähigkeit (Fruchtbarkeit)]	n-Hexan; f
<u>methyl methacrylate</u>	
Gefahr der Sensibilisierung der Haut	Methylmethacrylat; Sh

National legislation United Kingdom

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

28 / 30

BIKE7 LUBRICATE WET

BIKE7 LUBRICATE WET

No data available

National legislation Ireland

BIKE7 LUBRICATE WET

No data available

n-hexane

Skin resorption	n-Hexane; Skin
-----------------	----------------

methyl methacrylate

Dermal sensitisation	Methyl methacrylate; Sens.
Respiratory sensitisation	Methyl methacrylate; Sens.

Other relevant data

BIKE7 LUBRICATE WET

No data available

distillates (petroleum), hydrotreated light paraffinic

TLV - Carcinogen	Mineral oil, excluding metal working fluids: Pure, highly and severely refined; A4
------------------	--

Distillates (petroleum), solvent-dewaxed heavy paraffinic

TLV - Carcinogen	Mineral oil, excluding metal working fluids: Poorly and mildly refined; A2
------------------	--

Distillates (petroleum), hydrotreated heavy paraffinic

TLV - Carcinogen	Mineral oil, excluding metal working fluids: Pure, highly and severely refined; A4
------------------	--

Distillates (petroleum), solvent-dewaxed light paraffinic

TLV - Carcinogen	Mineral oil, excluding metal working fluids: Poorly and mildly refined; A2
------------------	--

n-hexane

TLV - Skin absorption	n-Hexane; Skin; Danger of cutaneous absorption
-----------------------	--

methyl methacrylate

TLV - Carcinogen	Methyl methacrylate; A4
IARC - classification	3; Methyl methacrylate
TLV - Skin Sensitisation	Methyl methacrylate; SEN; Sensitization

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H220 Extremely flammable gas.
- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs (nervous system) through prolonged or repeated exposure if inhaled.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH208 Contains a sensitising substance. May produce an allergic reaction.

(*)	INTERNAL CLASSIFICATION BY BIG
ADI	Acceptable daily intake
AOEL	Acceptable operator exposure level
ATE	Acute Toxicity Estimate
BCF	Bioconcentration Factor
BEI	Biological Exposure Indices
CLP (EU-GHS)	Classification, labelling and packaging (Globally Harmonised System in Europe)
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
EC10	Effect Concentration 10 %
EC50	Effect Concentration 50 %
ErC50	EC50 in terms of reduction of growth rate
GLP	Good Laboratory Practice
HS	Harmonized System of Nomenclature, a standardized international system for classifying goods under the Harmonized System Convention, as drawn up by the World Customs Organization Secretariat
LC0	Lethal Concentration 0 %
LC50	Lethal Concentration 50 %
LD50	Lethal Dose 50 %
LOAEC/LOAEL	Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level
NOAEC/NOAEL	No Observed Adverse Effect Concentration/No Observed Adverse Effect Level
NOEC/NOEL	No Observed Effect Concentration/No Observed Effect Level
OECD	Organisation for Economic Co-operation and Development

Reason for revision: 1; 3; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2007-07-31

Date of revision: 2026-06-02

Revision number: 0800

BIG number: 45278

29 / 30

BIKE7 LUBRICATE WET

PBT	Persistent, Bioaccumulative & Toxic
PNEC	Predicted No Effect Concentration
STP	Sludge Treatment Process
vPvB	very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.