## SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

## **BIKE7 DEBLOCK**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

Product name : BIKE7 DEBLOCK
Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant identified uses

Lubricant

## 1.2.2 Uses advised against

No uses advised against

## 1.3. Details of the supplier of the safety data sheet

## Supplier of the safety data sheet

BIKE 7\*

Industrielaan 5B

B-2250 Olen

**2** +32 14 23 72 03

**4** +32 14 85 97 38

info@bike7.be

\*BIKE 7 is a registered trademark of Novatech International N.V.

#### Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

**2** +32 14 85 97 37

**4** +32 14 85 97 38

info@novatech.be

## 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :

+32 14 58 45 45 (BIG)

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
STOT SE	category 3	H336: May cause drowsiness or dizziness.
Aquatic Chronic	category 2	H411: Toxic to aquatic life with long lasting effects.

## 2.2. Label elements







Contains: Kerosine (petroleum), hydrodesulfurized.

Signal word	Danger
H-statements	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects
P-statements	

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16

Revision number: 0800 (supersedes revision 0701 of 2023-06-12)

Publication date: 2000-05-17 Date of revision: 2025-07-10

BIG number: 32074

878-17438-072-en

1 / 13

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves, protective clothing and eye protection/face protection.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard Caution! Substance is absorbed through the skin

## SECTION 3: Composition/information on ingredients

## 3.1. Substances

Not applicable

## 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	lRemark	M-factors and ATE
Kerosine (petroleum), hydrodesulfurized 01-2119462828-25	64742-81-0 265-184-9	C≥25%	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(6)(10)	Constituent	
butane 01-2119474691-32	106-97-8 203-448-7	10% ≤C<25%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
propane 01-2119486944-21	74-98-6 200-827-9	10% ≤C<25%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	

<sup>(1)</sup> For H- and EUH-statements in full: see section 16

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

## General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

## After inhalation

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

## After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

## After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

## After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

## 4.2. Most important symptoms and effects, both acute and delayed

## 4.2.1 Acute symptoms

## After inhalation:

Dizziness. Drowsiness.

## After skin contact:

Tingling/irritation of the skin.

#### After eye contact: No effects known.

no ellects kilowii

## After ingestion:

No effects known.

## 4.2.2 Delayed symptoms

No effects known.

## 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17

Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 2 / 13

<sup>(2)</sup> Substance with a Community workplace exposure limit

<sup>(6)</sup> Enumerated in Annex VI of Regulation (EC) No. 1272/2008 but the classification has been adapted after evaluation of available test data

<sup>(10)</sup> Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

<sup>(21) 1,3-</sup>butadiene < 0.1%

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher.

Major fire: Quantities of water.

## 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

#### 5.3. Advice for firefighters

## 5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

## SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

## 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

## 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

## 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards.

## 7.2. Conditions for safe storage, including any incompatibilities

## 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Store in a cool area. Keep container in a well-ventilated place. Fireproof storeroom. Protect against frost. Keep out of direct sunlight.

## 7.2.2 Keep away from:

Heat sources, ignition sources.

## 7.2.3 Suitable packaging material:

Aerosol.

## 7.2.4 Non suitable packaging material:

No data available

## 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1 Occupational exposure

## a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2000-05-17

Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 3 / 13

## Belgium

Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Carburant pour les moteurs à réaction (en vapeur d' hydrocarbure total) : application limitée aux conditions d'exposition aux aérosols négligeable	Time-weighted average exposure limit 8 h	200 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3)	Time-weighted average exposure limit 8 h	1000 ppm

## France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non	800 ppm
	réglementaire indicative)	
	Time-weighted average exposure limit 8 h (VL: Valeur non	1900 mg/m <sup>3</sup>
	réglementaire indicative)	

## Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm <b>(1)</b>
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m³ <b>(1)</b>
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm <b>(1)</b>
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³ <b>(1)</b>

## (1) UF: 4 (II)

## Austria

Butan (beide Isomeren): n-Butan (R 600) Isobutan (R 600a)	Tagesmittelwert (MAK)	800 ppm
	Tagesmittelwert (MAK)	1900 mg/m³
	Kurzzeitwert 60(Mow) 3x (MAK)	1600 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3800 mg/m³
Propan (R 290)	Tagesmittelwert (MAK)	1000 ppm
	Tagesmittelwert (MAK)	1800 mg/m³
	Kurzzeitwert 60(Mow) 3x (MAK)	2000 ppm
	Kurzzeitwert 60(Mow) 3x (MAK)	3600 mg/m³

## UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m³

## **USA (TLV-ACGIH)**

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm	
•	construction (121 transport target)	1000 ppiii	
	Explosion hazard		
Kerosene/Jet fuels, as total hydrocarbon vapor	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	200 mg/m³ <b>(1)</b>	
Propane	See Appendix F: Minimal Oxygen Content; Simple asphyxiant, Explosion hazard		

<sup>(1) (</sup>P): Application restricted to conditions in which there are negligible aerosol exposures

## b) National biological limit values

If limit values are applicable and available these will be listed below.

## 8.1.2 Sampling methods

If applicable and available it will be listed below.

## 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

## 8.1.4 Threshold values

<u>DNEL/DMEL - Workers</u> <u>Kerosine (petroleum), hydrodesulfurized</u>

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	50 mg/m³	
	Acute local effects inhalation	250 g/m³	
	Long-term systemic effects dermal	7.7 mg/kg bw/day	

DNEL/DMEL - General population

Effect level (DNEL/DMEL) Type		Value	Remark
DNEL	Long-term systemic effects inhalation	10.66 mg/m³	
	Long-term systemic effects dermal	1.64 mg/kg bw/day	
	Long-term systemic effects oral	5 mg/m³	

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17 Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 4/13

#### 8.1.5 Control banding

If applicable and available it will be listed below.

#### 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

#### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

## a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

## b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

## 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical form	Aerosol
Colour	Black
Odour	Characteristic odour
Odour threshold	No data available in the literature
Melting point	Not applicable (aerosol)
Boiling point	No data available in the literature
Flammability	Extremely flammable aerosol.
Explosion limits	0.7 - 9.5 % ; Propellant
Flash point	Not applicable (aerosol)
Auto-ignition temperature	Not applicable (aerosol)
Decomposition temperature	No data available in the literature
рН	Not applicable (non-soluble in water)
Kinematic viscosity	Not applicable (aerosol)
Dynamic viscosity	Not applicable (aerosol)
Solubility	Water ; insoluble
Log Kow	Not applicable (mixture)
Vapour pressure	No data available in the literature
Absolute density	730 kg/m³
Relative density	0.73
Relative vapour density	No data available in the literature
Particle size	Not applicable (liquid)

## 9.2. Other information

No data available

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

## 10.2. Chemical stability

 $Stable\ under\ normal\ conditions.$ 

## 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

## **Precautionary measures**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

## 10.5. Incompatible materials

No data available.

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2000-05-17

Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 5 / 13

## 10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

## SECTION 11: Toxicological information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## 11.1.1 Test results

#### Acute toxicity

## **BIKE7 DEBLOCK**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD	> 5000 mg/kg bw		Rat (male /	Read-across	
		420			female)		
Dermal	LD50	Equivalent to OECD	> 2000 mg/kg bw	24 h	Rabbit (male /	Read-across	
		402			female)		
Inhalation (vapours)	LC50	Equivalent to OECD	> 5.28 mg/l air	4 h	Rat (male /	Read-across	
		403			female)		

## Conclusion

Not classified for acute toxicity

## Corrosion/irritation

## **BIKE7 DEBLOCK**

No (test)data on the mixture available

Classification is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating	EPA OTS 798.4500			Rabbit	Read-across	Single treatment
Skin	Irritating	US EPA	24 h	24; 48; 72 hours	Rabbit	Read-across	

## Conclusion

Causes skin irritation.

Not classified as irritating to the respiratory system

Not classified as irritating to the eyes

## Respiratory or skin sensitisation

## BIKE7 DEBLOCK

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 406		Guinea pig (male)	Read-across	

## Conclusion

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin

## Specific target organ toxicity

## BIKE7 DEBLOCK

No (test)data on the mixture available

Classification is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time		Value determination	Remark
Oral (stomach tube)	NOAEL	Equivalent to OECD 408	750 mg/kg bw/day	No effect	21 week(s)	Rat (female)	Read-across	
Dermal	NOAEL	Equivalent to OECD 411	≥ 495 mg/kg bw/day	No effect	13 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across	
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	≥ 1000 mg/m³ air	No effect	90 days (continuous)	Rat (female)	Read-across	
Inhalation			STOT SE cat.3	Drowsiness, dizziness			Literature study	

## Conclusion

May cause drowsiness or dizziness.

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17 Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 6 / 13

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

## **BIKE7 DEBLOCK**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					
Negative with metabolic	Equivalent to OECD 476	Mouse (lymphoma L5178Y	No effect	Read-across	
activation, negative		cells)			
without metabolic					
activation					

## Mutagenicity (in vivo)

## **BIKE7 DEBLOCK**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Result	Method	Exposure time	Test substrate	Organ/Effect	Value determination	Remark
Positive (Intraperitoneal)	Equivalent to OECD 479		Mouse (male)	Affection of the	Read-across	Single
				bone marrow		intraperitoneal
						injection
Negative (Intraperitoneal)	Equivalent to OECD 479		Mouse (female)	No effect	Read-across	Single
						intraperitoneal
						injection

## Conclusion

Not classified for mutagenic or genotoxic toxicity

## Carcinogenicity

## **BIKE7 DEBLOCK**

No (test)data on the mixture available

Judgement is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

Route of exposure	Parameter	Method	Value	Organ/Effect	Exposure time	Species	Value determination	Remark
Dermal		Equivalent to OECD 451		Skin (tumor formation)	104 week(s)	Mouse (male)	Read-across	

## $\underline{\textbf{Conclusion}}$

Not classified for carcinogenicity

## Reproductive toxicity

## **BIKE7 DEBLOCK**

No (test)data on the mixture available

Judgement is based on the relevant ingredients Kerosine (petroleum), hydrodesulfurized

Category	Parameter	Method	Value	Exposure time	Species	Effect	Value determination	Remark
Developmental toxicity (Oral (stomach tube))	NOAEL	OECD 414	1000 mg/kg bw/day	10 day(s)	Rat	Foetus (no effect)	Read-across	
Developmental toxicity (Oral (stomach tube))	LOAEL	OECD 414	1500 mg/kg bw/day	10 day(s)	Rat	Foetus (reduced fetal bodyweights)	Read-across	
Maternal toxicity (Oral (stomach tube))	NOAEL	OECD 414	500 mg/kg bw/day	10 day(s)	Rat	No effect	Read-across	
Maternal toxicity (Oral (stomach tube))	LOAEL	OECD 414	1000 mg/kg bw/day	10 day(s)	Rat	Maternal toxicity	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	Equivalent to OECD 415	≥ 1500 mg/kg bw/day	21 week(s)	Rat (female)	No effect	Read-across	
Effects on fertility (Oral (stomach tube))	NOAEL	Equivalent to OECD 415	≥ 3000 mg/kg bw/day	10 week(s) - 13 week(s)	Rat (male)	No effect	Read-across	

## Conclusion

Not classified for reprotoxic or developmental toxicity

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17 Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 7 / 13

## Aspiration hazard

**BIKE7 DEBLOCK** 

Judgement is based on the relevant ingredients Not classified for aspiration toxicity

### **Toxicity other effects**

**BIKE7 DEBLOCK** 

No (test)data on the mixture available

## Chronic effects from short and long-term exposure

BIKE7 DEBLOCK

No effects known.

## 11.2. Information on other hazards

No evidence of endocrine disrupting properties

# SECTION 12: Ecological information

## 12.1. Toxicity

**BIKE7 DEBLOCK** 

No (test)data on the mixture available

Classification is based on the relevant ingredients

Kerosine (petroleum), hydrodesulfurized

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	2 mg/l - 5 mg/l	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; GLP
Acute toxicity crustacea	EL50	OECD 202	1.4 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	1 mg/l - 3 mg/l	72 h	Selenastrum capricornutum	Static system	Fresh water	Experimental value; Cell numbers
Long-term toxicity aquatic crustacea	NOEL	Equivalent to OECD 211	0.48 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction

## Conclusion

Toxic to aquatic life with long lasting effects.

## 12.2. Persistence and degradability

Kerosine (petroleum), hydrodesulfurized

**Biodegradation water** 

Method	Value	Duration	Value determination
OECD 301F	59 %	28 day(s)	Experimental value

## Conclusion

Water

Contains non readily biodegradable component(s)

## 12.3. Bioaccumulative potential

## **BIKE7 DEBLOCK**

## Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

## Kerosine (petroleum), hydrodesulfurized

## Log Kow

Method	Remark	Value	Temperature	Value determination
EU Method A.8		6.3		Experimental value

## Conclusion

Contains bioaccumulative component(s)

## 12.4. Mobility in soil

Kerosine (petroleum), hydrodesulfurized

## Percent distribution

Method	Fraction air	 Fraction sediment	Fraction soil	Fraction water	Value determination
Fugacity Model	22 %	6.2 %	2.5 %	69 %	Calculated value
Level III					

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17
Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 8 / 13

#### Conclusion

Contains component(s) with potential for mobility in the soil

#### 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

#### 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

#### 12.7. Other adverse effects

#### **BIKE7 DEBLOCK**

#### Greenhouse gases

Contains component(s) included in the list of substances which may contribute to the greenhouse effect (IPCC)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

## Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

#### Kerosine (petroleum), hydrodesulfurized

## **Greenhouse** gases

Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 2024/573)

## Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 2024/590)

#### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

## 13.1. Waste treatment methods

### 13.1.1 Provisions relating to waste

#### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 08\* (waste engine, gear and lubricating oils: other engine, gear and lubricating oils). Depending on branch of industry and production process, also other waste codes may be applicable.

## 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Specific treatment. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

## 13.1.3 Packaging/Container

## **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## **SECTION** 14: Transport information

## Road (ADR)

14.1. UN number or ID number	
UN number	1950
14.2. UN proper shipping name	
Proper shipping name	aerosols
14.3. Transport hazard class(es)	
Hazard identification number	
Class	2
Classification code	5F
14.4. Packing group	
Packing group	
Labels	2.1
14. <u>5</u> . Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	liquids. A package shall not weigh more than 30 kg (gross mass).

## Rail (RID)

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16

Publication date: 2000-05-17

Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 9 / 13

BIKE7	' DEBLOCK
4.1. UN number or ID number	luce
UN number	1950
1.2. UN proper shipping name	aerosols
Proper shipping name 4.3. Transport hazard class(es)	ae103013
Hazard identification number	23
Class	2
Classification code	5F
4.4. Packing group	Σ1
Packing group	
Labels	2.1
1.5. Environmental hazards	
Environmentally hazardous substance mark	yes
1.6. Special precautions for user	
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo
	liquids. A package shall not weigh more than 30 kg (gross mass).
nd waterways (ADN)	
1.1. UN number or ID number	1050
UN number/ID number	1950
1.2. UN proper shipping name Proper shipping name	aerosols
	aciusuis
1.3. Transport hazard class(es) Class	2
Classification code	5F
	jor .
4.4. Packing group  Packing group	
Labels	2.1
1.5. Environmental hazards	2.1
Environmentally hazardous substance mark	yes
4.6. Special precautions for user	lyes .
Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg (gross mass).
(IMDG/IMSBC)	
4.1. UN number or ID number	
UN number	1950
4.2. UN proper shipping name	2500
Proper shipping name	aerosols
1.3. Transport hazard class(es)	
Class	2.1
1.4. Packing group	•
Packing group	
Labels	2.1
1.5. Environmental hazards	·
Marine pollutant	Р
Environmentally hazardous substance mark	yes
1.6. Special precautions for user	
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	381
Special provisions	63
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg (gross mass).
1.7. Maritime transport in bulk according to IMO instruments	indings: w backage shall not weigh more than 30 kg (Bross mass).
Annex II of MARPOL 73/78	Not applicable
ICAO-TI/IATA-DGR)	
4.1. UN number or ID number	
UN number/ID number	1950

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17
Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 10 / 13

14.2. UN proper shipping name	
Proper shipping name	aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
14.4. Packing group	
Packing group	
Labels	2.1
14.5. Environmental hazards	
Environmentally hazardous substance mark	yes
14.6. Special precautions for user	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport	
Limited quantities: maximum net quantity per packaging	30 kg G

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
69.26 %	
505.56 g/l	

## Directive 2012/18/EU (Seveso III)

Threshold values under normal circumstances

Substance or category	Low tier (tonnes)	Top tier (tonnes)		For this substance or mixture the summation rule has to be applied for:
P3b FLAMMABLE AEROSOLS	5000 (net)	50000 (net)	None	Flammability
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500	None	Eco-toxicity

## **REACH Candidate list**

Does not contain component(s) included in candidate list of substances of very high concern (SVHC) for authorisation (Article 59 of Regulation (EC) No 1907/2006)

## REACH Annex XIV - Authorisation

Does not contain component(s) included in Annex XIV of Regulation (EC) No 1907/2006: list of substances subject to authorisation

## REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

and use of certain dangerous :	substances, mixtures and articles.	,
	Designation of the substance, of the group of	Conditions of restriction
	substances or of the mixture	
· Kerosine (petroleum), hydrodesulfurized	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in:  — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,  — tricks and jokes,  — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,  2. Articles not complying with paragraph 1 shall not be placed on the market.  3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  — can be used as fuel in decorative oil lamps for supply to the general public, and,  — present an aspiration hazard and are labelled with H304,  4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp or even sucking the wick of lamps — may lead to life-threatening lung damage";  b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";  c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
· Kerosine (petroleum), hydrodesulfurized	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2,	Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17
Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 11 / 13

substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to th

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,— silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs.
- stink bombs.
- 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

"For professional users only".

- 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.
- The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

#### **National legislation Belgium**

**BIKE7 DEBLOCK** 

No data available

Kerosine (petroleum), hydrodesulfurized

Résorption peau	Carburant pour les moteurs à réaction (en vapeur d'hydrocarbure total) : application limitée aux conditions d'exposition
	aux aérosols négligeable; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux,
	constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par
	présence de l'agent dans l'air.

## **National legislation The Netherlands**

BIKE7 DEBLOCK

Waterbezwaarlijkheid A (2); Algemene Beoordelingsmethodiek (ABM)

## **National legislation France**

**BIKE7 DEBLOCK** 

No data available

#### **National legislation Germany**

**BIKE7 DEBLOCK** 

Lagerklasse (TRGS5	10) 2B: Aerosolpackungen und F	B: Aerosolpackungen und Feuerzeuge	
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017		
Kerosine (petroleum)	, hydrodesulfurized		
TA-Luft	5 2 5/1		

## **National legislation Austria**

BIKE7 DEBLOCK

No data available

## **National legislation United Kingdom**

BIKE7 DEBLOCK

No data available

## Other relevant data

**BIKE7 DEBLOCK** 

No data available Kerosine (petroleum), hydrodesulfurized

TLV - Carcinogen	Kerosene/Jet fuels, as total hydrocarbon vapor; A3
TLV - Skin absorption	Kerosene/Jet fuels, as total hydrocarbon vapor; Skin; Danger of cutaneous absorption

## 15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

## SECTION 16: Other information

## Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H226 Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

 $\ensuremath{\mathsf{H411}}\xspace$  Toxic to aquatic life with long lasting effects.

(\*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE Acute Toxicity Estimate

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17 Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 12 / 13

BCF Bioconcentration Factor
BEI Biological Exposure Indices

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC10 Effect Concentration 10 %
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

GLP Good Laboratory Practice
LC0 Lethal Concentration 0 %
LC50 Lethal Concentration 50 %
LD50 Lethal Dose 50 %

LOAEC/LOAEL Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level

NOAEC/NOAEL No Observed Adverse Effect Concentration/No Observed Adverse Effect Level

NOEC/NOEL No Observed Effect Concentration/No Observed Effect Level OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2.3; 3; 4; 5; 6; 7; 8; 11; 12; 15; 16 Publication date: 2000-05-17

Date of revision: 2025-07-10

Revision number: 0800 BIG number: 32074 13 / 13