





- Rust protection
- Water resistant
- Extreme conditions



Technical Info

- · Water solubility: insoluble.
- · State: thick liquid.
- · Odour: characteristic.
- · Viscosity at 20°C: 1300 mPA.s.
- · Vapour pressure at 20°C: 19000 Pa.
- Relative density at 20°C: 0.750.
- · Spontaneaous combustion: 365°C.
- Flashpoint: <-20°C.
- · Boiling point/range: 60-300°C.
- Temperature resistance: -45°C to +240°C.

Packing

Lubricate Quick Wet - 1 x 50ml 977030924 Lubricate Quick Wet - display 977050924

Product

Characteristics

- Lubricate Ouick Wet is a transparent lubricant with PTFE to eliminate friction long-term.
- Lubricate Quick Wet is an adhesive lubricant that can withstand high loads in difficult circumstances.
- The product will continue to work even after spraying. You can only remove it with Degrease.

Applications

• Suitable for all weather conditions, whenever guick lubrication is required.

Use

When applied to the chain links, the oil is very liquid in order to penetrate better into the chain and ensure that each axis of each link is well lubricated.

After a few minutes, the oil solidifies and adheres so that it does not run out of the chain when you are riding and continues to lubricate optimally even during long rides.

Since there is also some of that adhering oil on the outside of the chain, before riding or after a few minutes after lubricating (about ten for the spray cans, 3-4min for the Quick version), run the chain in a cloth to remove the oil on the outside of the chain so that your chain stays clean while riding.

It is recommended to degrease the transmission with Degrease or Chain Clean after a ride/race and apply a fresh layer of Lubricate.

Nb: It is always best to apply oil at the bottom behind the chainring. That way there is no oil running into the cassette and you avoid contact with the brake discs.

