## SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

# **BIKE7 CLEAN PH9**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : BIKE7 CLEAN PH9
Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant identified uses

Detergent according to Regulation (EC) No 648/2004

#### 1.2.2 Uses advised against

No uses advised against known

#### 1.3. Details of the supplier of the safety data sheet

## Supplier of the safety data sheet

BIKE 7\*

Industrielaan 5B

B-2250 Olen

**2** +32 14 23 72 03

**4** +32 14 85 97 38

info@bike7.be

\*BIKE 7 is a registered trademark of Novatech International N.V.

#### Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

**2** +32 14 85 97 37

**山** +32 14 85 97 38

info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch):

+32 14 58 45 45 (BIG)

## SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

classified as daffgerous according to the criteria of Regulation (LC) NO 1272/2008			
Class	Category	Hazard statements	
Eye Irrit.	category 2	H319: Causes serious eye irritation.	

## 2.2. Label elements



Signal word Warning

H-statements H319

Causes serious eye irritation.

P-statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear eye protection.

P264 Wash hands thoroughly after handling.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

#### 2.3. Other hazards

No other hazards known

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel

http://www.big.be © BIG vzw

Reason for revision: 2, 3, 8, 9, 12

rum voor gevaarlijke stoffen vzw (BIG) Publication date: 2015-04-23 Geel Date of revision: 2021-06-19

878-17438-022-

Revision number: 0300 BIG number: 56129 1 / 15

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
isotridecanol, ethoxylated	69011-36-5	C≤3%	Acute Tox. 4; H302 Eye Dam. 1; H318	(1)(10)	Constituent	
propan-2-ol 01-2119457558-25	67-63-0 200-661-7	C≤2%	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	(1)(2)(10)	Constituent	
2-butoxyethanol 01-2119475108-36	111-76-2 203-905-0	C≤2%	Acute Tox. 4; H332 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319	(1)(2)(10)	Constituent	ATE oral: 1200 mg/kg

<sup>(1)</sup> For H- and EUH-statements in full: see section 16

## SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

#### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

#### After eve contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

## 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

#### After inhalation:

No effects known.

#### After skin contact:

No effects known.

#### After eye contact:

Irritation of the eye tissue.

### After ingestion:

Vomiting. Abdominal pain. Diarrhoea. Headache.

## 4.2.2 Delayed symptoms

No effects known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting class B foam extinguisher, Quick-acting CO2 extinguisher. Major fire: Class B foam (alcohol-resistant), Water spray if puddle cannot expand.

#### 5.1.2 Unsuitable extinguishing media:

Small fire: Water (quick-acting extinguisher, reel); risk of puddle expansion.

Major fire: Water; risk of puddle expansion.

#### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed.

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23

Revision number: 0300 BIG number: 56129 2/15

Date of revision: 2021-06-19

<sup>(2)</sup> Substance with a Community workplace exposure limit

<sup>(10)</sup> Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

#### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

No specific fire-fighting instructions required.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

# SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

No naked flames.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

#### 6.2. Environmental precautions

Contain released product. Try to reduce evaporation.

#### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into inert absorbent material. Scoop absorbed substance into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

#### 6.4. Reference to other sections

See section 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 7.1. Precautions for safe handling

Keep away from naked flames/heat. Observe normal hygiene standards. Keep container tightly closed.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Protect against frost. Keep out of direct sunlight. Keep container tightly closed.

# 7.2.2 Keep away from:

Heat sources, oxidizing agents, reducing agents, (strong) acids, (strong) bases.

#### 7.2.3 Suitable packaging material:

No data available

## 7.2.4 Non suitable packaging material:

No data available

#### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

#### 8.1.1 Occupational exposure

## a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

2-Butoxyethanol	Time-weighted average exposure limit 8 h (Indicative occupational	20 ppm
	exposure limit value)	
	Time-weighted average exposure limit 8 h (Indicative occupational	98 mg/m³
	exposure limit value)	
	Short time value (Indicative occupational exposure limit value)	50 ppm
	Short time value (Indicative occupational exposure limit value)	246 mg/m <sup>3</sup>

Belgium

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2015-04-23

Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 3 / 15

2-Butoxyéthanol		Time-weighted average expos			20 ppm
		Time-weighted average expos	ure limit 8 h		98 mg/m <sup>3</sup>
		Short time value			50 ppm
Alcool isopropylique		Short time value	ura limit O h		246 mg/m
Accortisopropylique		Time-weighted average expos			200 ppm 500 mg/m
		Time-weighted average expos Short time value	ure illilit o II		400 ppm
		Short time value			1000 mg/
The Netherlands		phore time value			1000 1118/
The Netherlands 2-Butoxyethanol		Time-weighted average expos	ure limit 8 h (Public	occupational exposur	e 20 ppm
2 24.64/2		limit value)	are milit o ii (i abiic	occupational exposur	CIZO PPIII
		Time-weighted average expos	ure limit 8 h (Public	occupational exposur	e 100 mg/n
		Short time value (Public occup	ational exposure lir	nit value)	50 ppm
		Short time value (Public occup	ational exposure lir	nit value)	246 mg/n
France					
2-Butoxyéthanol		Time-weighted average expos	ure limit 8 h (VRC: V	/aleur réglementaire	10 ppm
		Time-weighted average exposicontraignante)	ure limit 8 h (VRC: V	/aleur réglementaire	49 mg/m <sup>3</sup>
		Short time value (VRC: Valeur	réglementaire cont	raignante)	50 ppm
		Short time value (VRC: Valeur			246 mg/m
Alcool isopropylique		Short time value (VL: Valeur n			400 ppm
		Short time value (VL: Valeur n			980 mg/n
Germany					
2-Butoxyethanol		Time-weighted average expos	ure limit 8 h /TRGS 9	900)	10 ppm
2 Batoxyethanor		Time-weighted average expos		•	49 mg/m <sup>3</sup>
Propan-2-ol		Time-weighted average expos	-	· ·	200 ppm
•		Time-weighted average expos	*	•	500 mg/n
,		, ,	,	•	<u> </u>
<b>UK</b> 2-Butoxyethanol		Time weighted average expec	ura limit 9 h (Markr	alaco ovnosuro limit	25 ppm
2-Butoxyethanoi		Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))		25 ppiii	
		Time-weighted average expos	ure limit 8 h (Workp	place exposure limit	123 mg/n
		(EH40/2005))			
		Short time value (Workplace e	exposure limit (EH40	)/2005))	50 ppm
		Short time value (Workplace e	· · · · · · · · · · · · · · · · · · ·		246 mg/m
Propan-2-ol		Time-weighted average exposure limit 8 h (Workplace exposure limit		400 ppm	
		(EH40/2005)) Time-weighted average exposure limit 8 h (Workplace exposure limit		999 mg/m	
		(EH40/2005))	are minic on (work	nace exposure minic	Jaga IIIg/II
		Short time value (Workplace	exposure limit (EH40	)/2005))	500 ppm
		Short time value (Workplace exposure limit (EH40/2005))		1250 mg/	
USA (TLV-ACGIH)			-		
2-Butoxyethanol		Time-weighted average expos	ure limit 8 h (TLV - A	Adopted Value)	20 ppm
2-propanol		Time-weighted average expos			200 ppm
		Short time value (TLV - Adopted Value)		400 ppm	
		Short time value (TLV - Adopte	•		
	e these will be listed b		,		
If limit values are applicable and available  Germany	Urin: expositionsend bei langzeitexpositio	elow. le, bzw. schichtende on: nach mehreren	150 mg/g Kreatinin		
If limit values are applicable and available  Germany  2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))	Urin: expositionsend	elow. le, bzw. schichtende n: nach mehreren hichten	150 mg/g		
If limit values are applicable and available  Germany  2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))  Propan-2-ol (Aceton)	Urin: expositionsend bei langzeitexpositio vorangegangenen sc Urin: expositionsend	elow. le, bzw. schichtende n: nach mehreren hichten	150 mg/g Kreatinin		
If limit values are applicable and available  Germany  2-Butoxyethanol (Butoxyessigsäure	Urin: expositionsend bei langzeitexpositio vorangegangenen sc Urin: expositionsend	elow. le, bzw. schichtende n: nach mehreren chichten le, bzw. schichtende	150 mg/g Kreatinin 25 mg/l		
If limit values are applicable and available  Germany  2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))  Propan-2-ol (Aceton)  Propan-2-ol (Aceton)	Urin: expositionsend bei langzeitexpositio vorangegangenen sc Urin: expositionsend	elow. le, bzw. schichtende n: nach mehreren chichten le, bzw. schichtende	150 mg/g Kreatinin 25 mg/l		
If limit values are applicable and available  Germany  2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))  Propan-2-ol (Aceton)  Propan-2-ol (Aceton)  UK  2-Butoxyethanol (butoxyacetic acid)	Urin: expositionsend bei langzeitexpositio vorangegangenen sc Urin: expositionsend Vollblut: expositions	elow. le, bzw. schichtende n: nach mehreren chichten le, bzw. schichtende	150 mg/g Kreatinin 25 mg/l 25 mg/l		
2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))  Propan-2-ol (Aceton)  Propan-2-ol (Aceton)  UK	Urin: expositionsend bei langzeitexpositio vorangegangenen sc Urin: expositionsend Vollblut: expositions	elow. le, bzw. schichtende n: nach mehreren chichten le, bzw. schichtende	150 mg/g Kreatinin 25 mg/l 25 mg/l	With hydrolysis	
If limit values are applicable and available Germany 2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))  Propan-2-ol (Aceton) Propan-2-ol (Aceton)  UK 2-Butoxyethanol (butoxyacetic acid)  USA (BEI-ACGIH) 2-buthoxyethanol (Butoxyacetic acid	Urin: expositionsend bei langzeitexpositio vorangegangenen sc Urin: expositionsend Vollblut: expositions	elow.  le, bzw. schichtende bn: nach mehreren chichten le, bzw. schichtende ende, bzw. schichtende	150 mg/g Kreatinin 25 mg/l 25 mg/l 240 mmol/mol creatinine	With hydrolysis Background, Nonspe	ecific
If limit values are applicable and available Germany 2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))  Propan-2-ol (Aceton) Propan-2-ol (Aceton)  UK 2-Butoxyethanol (butoxyacetic acid)  USA (BEI-ACGIH) 2-buthoxyethanol (Butoxyacetic acid (BAA))	Urin: expositionsend bei langzeitexpositio vorangegangenen sc. Urin: expositionsend Vollblut: expositions  Urine: post shift  urine: end of shift	elow.  le, bzw. schichtende bn: nach mehreren chichten le, bzw. schichtende ende, bzw. schichtende	150 mg/g Kreatinin  25 mg/l 25 mg/l  240 mmol/mol creatinine		ecific
If limit values are applicable and available Germany 2-Butoxyethanol (Butoxyessigsäure (nach Hydrolyse))  Propan-2-ol (Aceton) Propan-2-ol (Aceton)  UK 2-Butoxyethanol (butoxyacetic acid)  USA (BEI-ACGIH) 2-buthoxyethanol (Butoxyacetic acid (BAA)) 2-Propanol (Acetone)	Urin: expositionsend bei langzeitexpositio vorangegangenen sc. Urin: expositionsend Vollblut: expositions  Urine: post shift  urine: end of shift	elow.  le, bzw. schichtende bn: nach mehreren chichten le, bzw. schichtende ende, bzw. schichtende	150 mg/g Kreatinin  25 mg/l 25 mg/l  240 mmol/mol creatinine		ecific

Revision number: 0300 BIG number: 56129 4 / 15

Date of revision: 2021-06-19

Product name	Test	Number
2-Butoxyethanol (Butyl Cellosolve solvent)	OSHA	83
Butoxyacetic acid	NIOSH	8316
Butyl cellosolve (Volatile Organic compounds)	NIOSH	2549
Butyl Cellosolve	OSHA	83
Isopropanol (Volatile Organic compounds)	NIOSH	2549
Isopropyl Alcohol (Alcohols I)	NIOSH	1400
Isopropyl Alcohol	OSHA	109

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 Threshold values

#### **DNEL/DMEL - Workers**

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	500 mg/m³	
	Long-term systemic effects dermal	888 mg/kg bw/day	

#### 2-butoxyethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	98 mg/m³	
	Acute systemic effects inhalation	1091 mg/m³	
	Acute local effects inhalation	246 mg/m³	
	Long-term systemic effects dermal	125 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	

## DNEL/DMEL - General population

propan-2-ol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	89 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	319 mg/kg bw/day	
	Long-term systemic effects oral	26 mg/kg bw/day	

#### 2-butoxyethanol

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	59 mg/m³	
	Acute systemic effects inhalation	426 mg/m³	
	Acute local effects inhalation	147 mg/m³	
	Long-term systemic effects dermal	75 mg/kg bw/day	
	Acute systemic effects dermal	89 mg/kg bw/day	
	Long-term systemic effects oral	6.3 mg/kg bw/day	
	Acute systemic effects oral	26.7 mg/kg bw/day	

## PNEC

propan-2-ol

Compartments	Value	Remark
Fresh water	140.9 mg/l	
Fresh water (intermittent releases)	140.9 mg/l	
Marine water	140.9 mg/l	
STP	2251 mg/l	
Fresh water sediment	552 mg/kg sediment dw	
Marine water sediment	552 mg/kg sediment dw	
Soil	28 mg/kg soil dw	
Oral	160 mg/kg food	

### 2-butoxyethanol

Compartments	Value	Remark
Fresh water	8.8 mg/l	
Marine water	0.88 mg/l	
Fresh water (intermittent releases)	26.4 mg/l	
STP	463 mg/l	
Fresh water sediment	34.6 mg/kg sediment dw	
Marine water sediment	3.46 mg/kg sediment dw	
Soil	2.33 mg/kg soil dw	
Oral	20 mg/kg food	

## 8.1.5 Control banding

If applicable and available it will be listed below.

#### 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 8.2.1 Appropriate engineering controls

Keep away from naked flames/heat. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

## 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

a) Respiratory protection:

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23
Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 5 / 15

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034).

#### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical form	Liquid
Odour	Characteristic odour
Odour threshold	No data available in the literature
Colour	No data available on colour
Particle size	Not applicable (liquid)
Explosion limits	1.13 - 12.0 vol %
Flammability	Not classified as flammable
Log Kow	Not applicable (mixture)
Dynamic viscosity	1 mPa.s ; 20 °C
Kinematic viscosity	1 mm²/s ; 40 °C
Melting point	No data available in the literature
Boiling point	82 °C - 261 °C
Relative vapour density	No data available in the literature
Vapour pressure	43 hPa ; 20 °C
Solubility	Water ; soluble
Relative density	1.01 ; 20 °C
Absolute density	1013 kg/m³ ; 20 °C
Decomposition temperature	No data available in the literature
Auto-ignition temperature	230 °C
Flash point	65 °C
рН	9

### 9.2. Other information

Evaporation rate µ.3, butyr acetate	Evaporation rate	1.3; Butyl acetate	
-------------------------------------	------------------	--------------------	--

## SECTION 10: Stability and reactivity

## 10.1. Reactivity

Temperature above flashpoint: higher fire/explosion hazard.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No data available.

## 10.4. Conditions to avoid

#### **Precautionary measures**

Keep away from naked flames/heat.

#### 10.5. Incompatible materials

Oxidizing agents, reducing agents, (strong) acids, (strong) bases.

#### 10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

#### **Acute toxicity**

### BIKE7 CLEAN PH9

No (test)data on the mixture available Judgement is based on the relevant ingredients

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23

Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 6 / 15

isotridecanol, ethoxylated	

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	OECD 423	> 2000 mg/kg bw		Rat (male /	Experimental value	
					female)		
Oral			category 4			Literature study	
Dermal	LD50		5960 mg/kg bw	24 h	Rabbit (male)	Experimental value	
Inhalation (aerosol)	LC50	Equivalent to OECD	> 1.6 mg/l	4 h	Rat (male /	Experimental value	(maximum
		403			female)		achievable
							concentration)

#### propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50	Equivalent to OECD 401	5840 mg/kg bw		Rat	Experimental value	
Dermal	LD50	Equivalent to OECD 402	16400 ml/kg bw	24 h	Rabbit	Experimental value	
Dermal	LD50	Equivalent to OECD 402	12882 mg/kg bw	24 h	Rabbit	Experimental value	Converted value
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 10000 ppm	6 h	Rat (male / female)	Experimental value	

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	ATE		1200 mg/kg bw			Annex VI	
Oral	LD50	Equivalent to OECD 401	1746 mg/kg bw		Rat (male)	Experimental value	
Oral	LD50	OECD 401	1414 mg/kg bw		Guinea pig (male / female)	Experimental value	
Dermal	LD50	OECD 402	> 2000 mg/kg bw		Rat (male / female)	Experimental value	
Inhalation (vapours)	LC50		> 4.26 mg/l	4 h	Rat (male / female)	Experimental value	

The acute toxicity of this substance to rats, mice and rabbits is higher than it is to humans. Rats, mice and rabbits are highly susceptible to haemolysis following exposure to this substance and data from such species will overestimate the hazard to humans. Humans are not prone to such effects. The guinea pig is a much better model for predicting the hazard to humans.

## Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

#### **BIKE7 CLEAN PH9**

No (test)data on the mixture available

Classification is based on the relevant ingredients <u>isotridecanol</u>, <u>ethoxylated</u>

Route of exposure	Result	Method	Exposure time	Time point	 Value determination	Remark
Eye	Serious eye damage	OECD 405		24; 48; 72 hours	Experimental value	

propan-2-ol

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Eye		Equivalent to OECD 405		24 hours	Rabbit	Experimental value	Single treatment
Skin	Not irritating		4 h	4; 24; 48; 72 hours	Rabbit	Experimental value	

2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Irritating	OECD 405	24 h	24; 48; 72 hours	Rabbit	•	Single treatment with rinsing
Skin	Irritating	EU Method B.4	4 h	24; 48; 72 hours	Rabbit	Experimental value	

## Conclusion

Causes serious eye irritation.

Not classified as irritating to the skin

Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

## BIKE7 CLEAN PH9

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23 Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 7 / 15

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406		Guinea pig (male / female)	Experimental value	

2-butoxyethanol

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 406			Guinea pig (male / female)	Experimental value	

#### Conclusion

Not classified as sensitizing for skin Not classified as sensitizing for inhalation

## Specific target organ toxicity

## BIKE7 CLEAN PH9

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

<u> </u>								
Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
								determination
Oral								Data waiving
Dermal								Data waiving
Inhalation	NOAEC	OECD 451	5000 ppm		No effect	104 weeks (6h / day,	Rat (male /	Experimental
(vapours)						5 days / week)	female)	value
Inhalation	Dose level	Equivalent to	5000 ppm	Central	Drowsiness,	6 h	Rat (male /	Experimental
(vapours)		OECD 403		nervous	dizziness		female)	value
				system				

2-butoxyethanol

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	- •	Value determination
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 69 mg/kg bw/day		No effect	90 days (continuous)	Rat (male)	Experimental value
Oral (drinking water)	NOAEL	Equivalent to OECD 408	< 82 mg/kg bw/day		No effect	90 day(s)	Rat (female)	Experimental value
Dermal	NOAEL	Equivalent to OECD 411	> 150 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rabbit (male / female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	< 31 ppm		No effect	14 weeks (6h / day, 5 days / week)	Rat (female)	Experimental value
Inhalation (vapours)	NOAEC	Equivalent to OECD 413	62.5 ppm		No effect	14 weeks (6h / day, 5 days / week)	Rat (male)	Experimental value

## Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

## BIKE7 CLEAN PH9

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)	No effect	Experimental value	

2-butoxyethanol

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 471	Bacteria (S.typhimurium)		Experimental value	
Negative with metabolic activation, negative without metabolic activation	Equivalent to OECD 476	Chinese hamster ovary (CHO)		Experimental value	

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2015-04-23

Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 8 / 15

## Mutagenicity (in vivo)

#### BIKE7 CLEAN PH9

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD		Mouse (male / female)		Experimental value
	474				

2-butoxyethanol

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Intraperitoneal)	Equivalent to OECD	3 dose(s)/24-hour	Mouse (male)		Experimental value
	474	interval			

#### Conclusion

Not classified for mutagenic or genotoxic toxicity

#### Carcinogenicity

#### BIKE7 CLEAN PH9

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Route of exposure	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Inhalation (vapours)	NOEL	OECD 451	5000 ppm	104 weeks (6h / day, 5 days / week)	, ,	No carcinogenic effect		Experimental value

2-butoxyethanol

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation	NOAEC	Equivalent to	> 125 ppm	104 weeks (6h / day,	Rat (male /	No carcinogenic		Experimental value
(vapours)		OECD 451		5 days / week)	female)	effect		

## Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

## BIKE7 CLEAN PH9

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
							determination
NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect	Foetus	Experimental value
NOAEL	Equivalent to OECD 414	400 mg/kg bw/day	10 day(s)	Rat	No effect		Experimental value
NOAEL	Equivalent to OECD 415	853 mg/kg bw/day	21 day(s) - 70 day (s)	Rat (male / female)	No effect		Experimental value
	NOAEL	NOAEL Equivalent to OECD 414  NOAEL Equivalent to OECD 414  NOAEL Equivalent to	NOAEL Equivalent to OECD 414 bw/day  NOAEL Equivalent to OECD 414 bw/day  NOAEL Equivalent to OECD 414 bw/day  NOAEL Equivalent to 853 mg/kg	NOAEL         Equivalent to OECD 414         400 mg/kg bw/day         10 day(s)           NOAEL         Equivalent to OECD 414         400 mg/kg bw/day         10 day(s)           NOAEL         Equivalent to OECD 414         bw/day         21 day(s) - 70 day	NOAEL         Equivalent to OECD 414         400 mg/kg bw/day         10 day(s)         Rat bw/day           NOAEL         Equivalent to OECD 414         400 mg/kg bw/day         10 day(s)         Rat bw/day           NOAEL         Equivalent to S53 mg/kg         21 day(s) - 70 day         Rat (male /	NOAEL Equivalent to OECD 414 bw/day 10 day(s) Rat No effect bw/day  NOAEL Equivalent to OECD 414 bw/day 10 day(s) Rat No effect bw/day  NOAEL Equivalent to B53 mg/kg 21 day(s) - 70 day Rat (male / No effect	NOAEL Equivalent to OECD 414 bw/day 10 day(s) Rat No effect Foetus  NOAEL Equivalent to OECD 414 bw/day 10 day(s) Rat No effect  OECD 414 bw/day 10 day(s) Rat No effect  NOAEL Equivalent to 853 mg/kg 21 day(s) - 70 day Rat (male / No effect

2-butoxyethanol

	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
Developmental toxicity (Oral (stomach tube))	NOAEC	Equivalent to OECD 414	200 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect		Experimental value
Maternal toxicity (Oral (stomach tube))	NOAEL	Equivalent to OECD 414	30 mg/kg bw/day	3 days (gestation, daily)	Rat	No effect		Experimental value
Effects on fertility (Oral (drinking water))	NOAEL	Fertility Assessment	720 mg/kg bw/day	14 weeks (daily)	Mouse (male / female)	No effect		Experimental value

## Conclusion

Not classified for reprotoxic or developmental toxicity

## **Toxicity other effects**

### BIKE7 CLEAN PH9

No (test)data on the mixture available

## Chronic effects from short and long-term exposure

## BIKE7 CLEAN PH9

No effects known.

#### 11.2. Information on other hazards

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23
Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 9 / 15

No evidence of endocrine disrupting properties

# SECTION 12: Ecological information

## 12.1. Toxicity

**BIKE7 CLEAN PH9** 

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	Equivalent to OECD 203	9640 mg/l - 10000 mg/l	96 h	Pimephales promelas	Flow- through system	Fresh water	Experimental value; Lethal
Acute toxicity crustacea	LC50	Equivalent to OECD 202	> 10000 mg/l	24 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	Toxicity threshold		1800 mg/l	7 day(s)	Scenedesmus quadricauda	Static system	Fresh water	Experimental value; Toxicity test
Long-term toxicity fish								Data waiving
Long-term toxicity aquatic crustacea	NOEC		2344 μmol/l	16 day(s)	Daphnia magna		Fresh water	Experimental value; Growth
Toxicity aquatic micro- organisms	Toxicity threshold	Equivalent to DIN 38412/8	1050 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Toxicity test
	EC50	ISO 8192	41676 mg/l	30 minutes	Activated sludge			Experimental value

2-butoxyethanol

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50	OECD 203	1474 mg/l	96 h	Oncorhynchus mykiss	Static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EC50	OECD 202	1550 mg/l	48 h	Daphnia magna	Static system	Fresh water	Experimental value; Locomotor effect
Toxicity algae and other aquatic plants	ErC50	OECD 201	1840 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; Nominal concentration
	NOEC	OECD 201	286 mg/l	72 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Experimental value; Growth rate
Long-term toxicity fish	NOEC	Equivalent to OECD 204	> 100 mg/l	21 day(s)	Danio rerio	Semi-static system	Fresh water	Experimental value; Nominal concentration
Long-term toxicity aquatic crustacea	NOEC	OECD 211	100 mg/l	21 day(s)	Daphnia magna	Semi-static system	Fresh water	Experimental value; Reproduction
Toxicity aquatic micro- organisms	Toxicity threshold	Equivalent to DIN 38412/8	700 mg/l	16 h	Pseudomonas putida	Static system	Fresh water	Experimental value; Nominal concentration

#### Conclusion

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

## 12.2. Persistence and degradability

isotridecanol, ethoxylated

**Biodegradation water** 

Method	Value	Duration	Value determination
OECD 301B	82 %	28 day(s)	Experimental value

propan-2-ol

Biodegradation water

 Method
 Value
 Duration
 Value determination

 EU Method C.5
 53 %; Oxygen consumption
 5 day(s)
 Experimental value

Ρ	Phototransformation air (DT50 air)						
	Method	Value	Conc. OH-radicals	Value determination			
	AOPWIN v1.92	17.668 h	1.5E6 /cm³	Calculated value			

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23
Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 10 / 15

#### 2-butoxyethanol

**Biodegradation water** 

Method	Value	Duration	Value determination
OECD 301B	90.4 %; Carbon dioxide	28 day(s)	Experimental value

Phototransformation air (DT50 air)

Method	Value	Conc. OH-radicals	Value determination
AOPWIN v1.90	5.459 h	1.5E6 /cm³	QSAR

#### Conclusion

#### Water

Contains readily biodegradable component(s)

The surfactant(s) is/are biodegradable according to Regulation (EC) No 648/2004

#### 12.3. Bioaccumulative potential

#### BIKE7 CLEAN PH9

#### Log Kow

Method	Remark	Value	Temperature	Value determination	
	Not applicable (mixture)				

#### isotridecanol, ethoxylated

#### **BCF** fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		232.5 l/kg	54 h - 72 h	Pimephales promelas	Experimental value

#### **Log Kow**

Method	Remark	Value	Temperature	Value determination
OECD 117			22 °C	Weight of evidence approach

#### propan-2-ol

#### Log Kow

Method	Remark	Value	Temperature	Value determination
			25 °C	Weight of evidence approach

#### 2-butoxyethanol

#### **BCF** fishes

Parai	meter	Method	Value	Duration	Species	Value determination
						Data waiving

#### Log Kow

Method	Remark	Value	Temperature	Value determination
BASF test		IN 91	25 °C	Experimental value

## Conclusion

Does not contain bioaccumulative component(s)

## 12.4. Mobility in soil

isotridecanol, ethoxylated

## (log) Koc

Parameter	Method	Value	Value determination
log Koc		2.376 - 2.645	QSAR
			L -

#### propan-2-ol

# (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.185 - 0.541	Calculated value

## 2-butoxyethanol

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc	SRC PCKOCWIN v2.0	0.451 - 0.882	Calculated value

## Percent distribution

Method	Fraction air		Fraction sediment	Fraction soil	Fraction water	Value determination
	0.31 %	0 %	0.01 %	0.59 %	99.09 %	QSAR

## Conclusion

Contains component(s) with potential for mobility in the soil

#### 12.5. Results of PBT and vPvB assessment

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

## 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

## 12.7. Other adverse effects

BIKE7 CLEAN PH9

Greenhouse gases

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2015-04-23

Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 11 / 15

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

#### Water ecotoxicity pH

pH shift

isotridecanol, ethoxylated

#### Groundwater

Groundwater pollutant

propan-2-ol

#### Groundwater

Groundwater pollutant

2-butoxyethanol

#### Groundwater

Groundwater pollutant

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

#### **European Union**

Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

20 01 30 (separately collected fractions (except 15 01): detergents other than those mentioned in 20 01 29). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Remove waste in accordance with local and/or national regulations. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

## 13.1.3 Packaging/Container

#### **European Union**

Waste material code packaging (Directive 2008/98/EC).

15 01 02 (plastic packaging).

## SECTION 14: Transport information

## Road (ADR), Rail (RID), Inland waterways (ADN), Sea (IMDG/IMSBC), Air (ICAO-TI/IATA-DGR)

14.1. ON number		
Transport	Not subject	
14.2. UN proper shipping name		
14.3. Transport hazard class(es)		
Hazard identification number		
Class		
Classification code		
14.4. Packing group		
Packing group		
Labels		
14.5. Environmental hazards		
Environmentally hazardous substance mark	no	
14.6. Special precautions for user		
Special provisions		
Limited quantities		
14.7. Maritime transport in bulk according to IMO instrument	is	
Annex II of MARPOL 73/78	Not applicable, based on available data	

## SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture <a href="European legislation:"><u>European legislation:</u></a>

VOC content Directive 2010/75/EU

VOC content	Remark
3.20 %	
32.367 g/l	

Indicative occupational exposure limit values (Directive 98/24/EC, 2000/39/EC, 2004/37/EC and amendments)

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23
Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 12 / 15

#### 2-butoxyethanol

Product name	Skin resorption
2-Butoxyethanol	Skin

Ingredients according to Regulation (EC) No 648/2004 and amendments

 $<\!5\%\ phosphates, <\!5\%\ non-ionic\ surfactants,\ perfumes,\ limonene,\ cinnamal$ 

#### **REACH Annex XVII - Restriction**

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
isotridecanol, ethoxylated propan-2-ol 2-butoxyethanol	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:  (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;  (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;  (c) hazard class 4.1;  (d) hazard class 5.1.	1. Shall not be used in:  — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,  — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,  2. Articles not complying with paragraph 1 shall not be placed on the market.  3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with H304,  4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage";  b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";  c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
propan-2-ol	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:  — metallic glitter intended mainly for decoration,  — artificial snow and frost,  — "whoopee" cushions,  — silly string aerosols,  — imitation excrement,  — horns for parties,  — decorative flakes and foams,  — artificial cobwebs,  — stink bombs.  2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  "For professional users only".  3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.  4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.
propan-2-ol 2-butoxyethanol	Substances falling within one or more of the following points:  (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:  — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, but excluding any such substances classified due to effects only following exposure by inhalation  — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation  — skin sensitiser category 1, 1A or 1B  — skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2  — serious eye damage category 1 or eye irritant category 2  (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/208

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23
Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129

13 / 15

Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (d) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry.

#### **National legislation Belgium**

BIKE7 CLEAN PH9

No data available

2-butoxyethanol

Résorption peau	2-Butoxyéthanol; D; La mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux,
	constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par
	présence de l'agent dans l'air.

# National legislation The Netherlands BIKE7 CLEAN PH9

Waterbezwaarlijkheid	B (5); Algemene Beoordelingsmethodiek (ABM)
2-butoxyethanol	
Huidopname (wettelijk)	2-Butoxyethanol; H

## National legislation France

**BIKE7 CLEAN PH9** 

No data available

2	-butoxyethanol	
	Risque de pénétration	2-Butoxyéthanol; Risque de pénétration percutanée
	percutanée	

# National legislation Germany BIKE7 CLEAN PH9

Lagerklasse (TRGS510)	10: Brennbare Flüssigkeiten die keiner der vorgenannten LGK zuzuordnen sind			
WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017			
isotridecanol, ethoxylated				
TA-Luft	5.2.5/I			
propan-2-ol				
TA-Luft	5.2.5			
TRGS900 - Risiko der	Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen			
Fruchtschädigung	Grenzwertes nicht befürchtet zu werden			
2-butoxyethanol				
TA-Luft	5.2.5/I			
TRGS900 - Risiko der	2-Butoxyethanol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des			
Fruchtschädigung	biologischen Grenzwertes nicht befürchtet zu werden			

## **National legislation United Kingdom**

Hautresorptive Stoffe

BIKE7 CLEAN PH9

No data available

2-butoxyethanol

ICI.in alternation In District and City	
ISKIII ADSOLDLIOII IZ-DULOXVELIIAIIOI. SK	

# Other relevant data BIKE7 CLEAN PH9

No data available

propan-2-ol

IARC - classification	3; Isopropanol	
TLV - Carcinogen	2-propanol; A4	
2-butoxyethanol		
IARC - classification	3; 2-butoxyethanol	
TLV - Carcinogen	2-Butoxyethanol: A3	

## 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23

2-Butoxyethanol; H; Hautresorptiv

Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 14 / 15

## SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

(\*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE Acute Toxicity Estimate

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2015-04-23
Date of revision: 2021-06-19

Revision number: 0300 BIG number: 56129 15 / 15