# SAFETY DATA SHEET



Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

# **BIKE7 LUBRICATE DRY**

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : BIKE7 LUBRICATE DRY
Registration number REACH : Not applicable (mixture)

Product type REACH : Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1 Relevant identified uses

Lubricant

#### 1.2.2 Uses advised against

No uses advised against

#### 1.3. Details of the supplier of the safety data sheet

#### Supplier of the safety data sheet

BIKE 7\*

Industrielaan 5B

B-2250 Olen

**2** +32 14 23 72 03

**4** +32 14 85 97 38

info@bike7.be

\*BIKE 7 is a registered trademark of Novatech International N.V.

#### Manufacturer of the product

Novatech International N.V.

Industrielaan 5B

B-2250 Olen

**2** +32 14 85 97 37

**4** +32 14 85 97 38

info@novatech.be

#### 1.4. Emergency telephone number

24h/24h (Telephone advice: English, French, German, Dutch) :

+32 14 58 45 45 (BIG)

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Skin Irrit.	category 2	H315: Causes skin irritation.
Aquatic Chronic	category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements





Sigilai	WUI	u
H-stat	eme	nts

Danger

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.

P-statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG)

Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be

© BIG vzw

Reason for revision: 2, 3, 8, 9, 12

Revision number: 0400

Publication date: 2006-12-14 Date of revision: 2021-06-19 878-17438-022-en

P280 Wear protective gloves, protective clothing and eye protection/face protection.

P264 Wash hands thoroughly after handling.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulation.

#### 2.3. Other hazards

Gas/vapour spreads at floor level: ignition hazard

# SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name REACH Registration No	CAS No EC No List No	Conc. (C)	Classification according to CLP	Note	Remark	M-factors and ATE
butane	106-97-8 203-448-7	C≤30%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)(21)	Propellant	
propane 01-2119486944-21	74-98-6 200-827-9	C≤20%	Flam. Gas 1A; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant	
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics 01-2119475515-33	927-510-4	C≤7%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(2)(10)	Constituent	
hydrocarbons, C6, isoalkanes, < 5% n-hexane 01-2119484651-34	931-254-9	C≤5%	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	(1)(10)	Constituent	
n-hexane 01-2119480412-44	110-54-3 203-777-6	C≤0.3%	Flam. Liq. 2; H225 Repr. 2; H361f Asp. Tox. 1; H304 STOT RE 2; H373 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411 STOT RE 2; H373: C≥5%, (CLP Annex VI (ATP 0I)	(1)(2)(10)	Constituent	

<sup>(1)</sup> For H- and EUH-statements in full: see section 16

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

# SECTION 4: First aid measures

#### 4.1. Description of first aid measures

#### General

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

#### After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

### After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

## After eye contact:

Rinse immediately with (lukewarm) water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

#### After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

After inhalation:

No effects known.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14

Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 2 / 16

<sup>(2)</sup> Substance with a Community workplace exposure limit

<sup>(10)</sup> Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

<sup>(21) 1,3-</sup>butadiene < 0.1%

No effects known.

After ingestion:

No effects known.

#### 4.2.2 Delayed symptoms

No effects known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### 5.1.1 Suitable extinguishing media:

Small fire: Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher.

Major fire: Adapt extinguishing media to the environment for surrounding fires.

#### 5.1.2 Unsuitable extinguishing media:

Small fire: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), Foam.

Major fire: Water (water can be used to control jet flame), Foam.

#### 5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

#### 5.3. Advice for firefighters

#### 5.3.1 Instructions:

Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. If exposed to fire cool the closed containers by spraying with water. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.

#### 5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: self-contained breathing apparatus (EN 136 + EN 137).

# SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosion proof appliances and lighting equipment.

#### 6.1.1 Protective equipment for non-emergency personnel

See section 8.2

#### 6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034).

Suitable protective clothing

See section 8.2

#### 6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

#### 6.3. Methods and material for containment and cleaning up

Take up liquid spill into absorbent material. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

### 6.4. Reference to other sections

See section 13.

# SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Do not discharge the waste into the drain.

#### 7.2. Conditions for safe storage, including any incompatibilities

# 7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Protect against frost. Keep out of direct sunlight.

#### 7.2.2 Keep away from:

Heat sources, ignition sources.

#### 7.2.3 Suitable packaging material:

Aerosol.

#### 7.2.4 Non suitable packaging material:

No data available

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2006-12-14

Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 3 / 16

### 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

n-Hexane	Time-weighted average exposure limit 8 h (Indicative occupational	20 ppm
	exposure limit value)	
	Time-weighted average exposure limit 8 h (Indicative occupational	72 mg/m <sup>3</sup>
	exposure limit value)	

#### Belgium

Delgium		
Butane, tous isomères: n-butane	Short time value	980 ppm
	Short time value	2370 mg/m <sup>3</sup>
Hydrocarbures aliphatiques sous forme gazeuse:	Time-weighted average exposure limit 8 h	1000 ppm
(Alcanes C1-C3)		
n-Hexane	Time-weighted average exposure limit 8 h	20 ppm
	Time-weighted average exposure limit 8 h	72 mg/m <sup>3</sup>

#### The Netherlands

Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	20 ppm
Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	72 mg/m³
Short time value (Public occupational exposure limit value)	40 ppm
Short time value (Public occupational exposure limit value)	144 mg/m³

#### France

n-Butane	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	800 ppm
	Time-weighted average exposure limit 8 h (VL: Valeur non réglementaire indicative)	1900 mg/m³
n-Hexane	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	20 ppm
	Time-weighted average exposure limit 8 h (VRC: Valeur réglementaire contraignante)	72 mg/m <sup>3</sup>

#### Germany

Butan	Time-weighted average exposure limit 8 h (TRGS 900)			
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m <sup>3</sup>		
n-Hexan	Time-weighted average exposure limit 8 h (TRGS 900) 50 p			
	Time-weighted average exposure limit 8 h (TRGS 900)	180 mg/m³		
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm		
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m³		

### UK

Butane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	600 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	1450 mg/m <sup>3</sup>
	Short time value (Workplace exposure limit (EH40/2005))	750 ppm
	Short time value (Workplace exposure limit (EH40/2005))	1810 mg/m³
n-Hexane	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	20 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	72 mg/m <sup>3</sup>

### USA (TLV-ACGIH)

Butane, isomers	Short time value (TLV - Adopted Value)	1000 ppm
n-Hexane	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	50 ppm

# b) National biological limit values

If limit values are applicable and available these will be listed below.

## Germany

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14
Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 4 / 16

Hexan (n-Hexan) (2,5-Hexandion plus	Urin: expositionsende, bzw. schichtende	5 mg/l	
4,5-Dihydroxy-2-Hexanon (nach			
Hydrolyse))			

#### **USA (BEI-ACGIH)**

n-Hexane (2,5-Hexanedione)	Urine: end of shift	0,5 mg/L	Without hydrolysis
----------------------------	---------------------	----------	--------------------

#### 8.1.2 Sampling methods

Product name	Test	Number
n-Hexane (Hydrocarbons, BP36 to 126C)	NIOSH	1500
n-Hexane (organic and inorganic gases by Extractive FTIR)	NIOSH	3800
n-Hexane (Volatile Organic compounds)	NIOSH	2549
n-Hexane	OSHA	2248
n-Hexane	OSHA	7

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 Threshold values

<u>DNEL/DMEL - Workers</u> hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL) Type		Value	Remark
DNEL	Long-term systemic effects inhalation	2085 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	300 mg/kg bw/day	

#### hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	5306 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	13964 mg/kg bw/day	

#### n-hexane

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	75 mg/m <sup>3</sup>	
	Long-term systemic effects dermal	11 mg/kg bw/day	

<u>DNEL/DMEL - General population</u> hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Effect level (DNEL/DMEL)	Туре	Value	Remark
DNEL	Long-term systemic effects inhalation	447 mg/m³	
	Long-term systemic effects dermal	149 mg/kg bw/day	
	Long-term systemic effects oral	149 mg/kg bw/day	

#### hydrocarbons, C6, isoalkanes, < 5% n-hexane

Effect level (DNEL/DMEL) Type		Value	Remark
DNEL Long-term systemic effects inhalation		1131 mg/m³	
	Long-term systemic effects dermal	1377 mg/kg bw/day	
	Long-term systemic effects oral	1301 mg/kg bw/day	

#### <u>n-hexane</u>

Effect level (DNEL/DMEL) Type		Value	Remark
DNEL	Long-term systemic effects inhalation	16 mg/m³	
	Long-term systemic effects dermal	5.3 mg/kg bw/day	
	Long-term systemic effects oral	4 mg/kg bw/day	

#### 8.1.5 Control banding

If applicable and available it will be listed below.

### 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

#### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Do not eat, drink or smoke during work.

#### a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

#### b) Hand protection:

Protective gloves against chemicals (EN 374).

Materials	Measured breakthrough time	Thickness	Protection index	Remark
nitrile rubber	> 480 minutes	0.35 mm	Class 6	

#### c) Eye protection:

Protective goggles (EN 166).

#### d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

#### 8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14 Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 5/16

# SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

ni i ić				
Physical form	Aerosol			
Odour	Characteristic odour			
Odour threshold	No data available in the literature			
Colour	No data available on colour			
Particle size	Not applicable (aerosol)			
Explosion limits	1.1 - 7.4 vol %			
Flammability	Extremely flammable aerosol.			
Log Kow	Not applicable (mixture)			
Dynamic viscosity	1 mPa.s ; 20 °C ; Liquid			
Kinematic viscosity	1 mm²/s ; 20 °C ; Liquid			
Melting point	ot applicable (aerosol)			
Boiling point	-42 °C1 °C ; Liquid			
Relative vapour density	>1			
Vapour pressure	19 hPa ; 20 °C ; Propellant			
Solubility	Water ; insoluble			
Relative density	0.87 ; 20 °C ; Liquid			
Absolute density	870 kg/m³ ; 20 °C ; Liquid			
Decomposition temperature	No data available in the literature			
Auto-ignition temperature	Not applicable (aerosol)			
Flash point	Not applicable (aerosol)			
рН	Not applicable (non-soluble in water)			

#### 9.2. Other information

9 ; Butyl acetate

# SECTION 10: Stability and reactivity

#### 10.1. Reactivity

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

#### 10.2. Chemical stability

Unstable on exposure to heat.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

#### **Precautionary measures**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

#### 10.5. Incompatible materials

No data available.

#### 10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

# SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### 11.1.1 Test results

#### **Acute toxicity**

#### **BIKE7 LUBRICATE DRY**

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Exposure time		Value determination	Remark
Oral	LD50		> 5840 mg/kg bw		Rat (male / female)	Read-across	
Dermal	LD50		> 2800 mg/kg bw	24 h	Rat (male / female)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 23.3 mg/l air	4 h	Rat (male / female)	Read-across	

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14 Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 6/16

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	> 16750 mg/kg bw		Rat (male)	Read-across	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	259.354 mg/l	4 h	Rat (male)	Read-across	

n-hexane

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value	Remark
						determination	
Oral	LD50	Equivalent to OECD 401	16000 mg/kg bw		Rat (male / female)	Experimental value	
Dermal	LD50	Equivalent to OECD 402	> 3350 mg/kg bw	4 h	Rabbit (male)	Read-across	
Inhalation (vapours)	LC50	Equivalent to OECD 403	> 17.6 mg/l air	24 h	Rat (male)	Experimental value	

### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

### BIKE7 LUBRICATE DRY

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating			7 days			Single treatment
Skin	Irritating	Equivalent to OECD 404	4 h	24; 48; 72 hours	Rabbit	Read-across	

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	Exposure time	Time point		Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405	72 h	72 hours	Rabbit	Read-across	
Skin	Slightly irritating	OECD 404	4 h	24; 48; 72 hours		Experimental value	

n-ł	าеха	ne

Route of exposure	Result	Method	Exposure time	Time point	Species	Value	Remark
						determination	
Еуе		Equivalent to OECD 405		72 hours	Rabbit	Read-across	
Skin	• ,	Equivalent to OECD 404	24 h	24; 72 hours	Rabbit	Read-across	
Skin	Irritating; category 2					Annex VI	

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

# Conclusion

Causes skin irritation.

Not classified as irritating to the eyes

#### Respiratory or skin sensitisation

#### **BIKE7 LUBRICATE DRY**

No (test)data on the mixture available  $\,$ 

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Result	Method	Exposure time	Observation time	Species	Value determination	Remark
				point			
Skin	Not sensitizing	Equivalent to OECD		24; 48 hours	Guinea pig (male	Read-across	
		406			/ female)		

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429		Mouse (male / female)	Read-across	

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14
Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 7 / 16

<u>n-hexane</u>

Route of exposure	Result	Method	 Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	Equivalent to OECD 429		Mouse	Read-across	

#### Conclusion

Not classified as sensitizing for skin

#### Specific target organ toxicity

#### BIKE7 LUBRICATE DRY

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Inhalation (vapours)	NOAEL	Equivalent to OECD 413	12350 mg/m³ air			26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across
Inhalation (vapours)	LOAEL	Equivalent to OECD 413	1650 mg/m³ air	Central nervous system		26 weeks (6h / day, 5 days / week)	Rat (male / female)	Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time		Value determination
Dermal								Data waiving
Inhalation	NOAEC	Equivalent to	10504 mg/m <sup>3</sup>		No effect	13 weeks (6h / day,	Rat (male)	Read-across
(vapours)		OECD 413	air			5 days / week)		
Inhalation	LOAEC	Equivalent to	31652 mg/m <sup>3</sup>	Liver; kidney	Organ	13 weeks (6h / day,	Rat (male)	Read-across
(vapours)		OECD 413	air		damage	5 days / week)		

n-hexane

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral (stomach tube)	NOAEL	Subchronic toxicity test	567 mg/kg bw/day - 1135 mg/kg bw/day		No effect	13 weeks (5 days / week)	Rat (male)	Experimental value
Oral (stomach tube)	LOAEL	Subchronic toxicity test	3956 mg/kg bw/day	Central nervous system	neurotoxic effects	17 weeks (5 days / week)	Rat (male)	Experimental value
Dermal								Data waiving
Inhalation (vapours)	LOAEC	Subchronic toxicity test	3000 ppm	Central nervous system	neurotoxic effects	16 weeks (daily)	Rat (male)	Experimental value
Inhalation (vapours)			STOT SE cat.3		Drowsiness, dizziness			Annex VI

# Conclusion

Not classified for subchronic toxicity

### Mutagenicity (in vitro)

# BIKE7 LUBRICATE DRY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	OECD 476	Human lymphocytes	No effect	Read-across	
activation, negative					
without metabolic					
activation					

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative with metabolic	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Read-across	
activation, negative					
without metabolic					
activation					

n-hexane

Result	Method	Test substrate	Effect	Value determination	Remark
Negative	OECD 476		No effect	Experimental value	
		cells)			
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Experimental value	

#### Mutagenicity (in vivo)

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14

Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 8/16

### BIKE7 LUBRICATE DRY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))	Equivalent to OECD	5 days (6h / day)	Rat (male / female)	Bone marrow	Experimental value
	475				

#### n-hexane

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative (Inhalation (vapours))		8 weeks (6h / day, 5	Mouse (male)		Experimental value
		days / week)			

#### Conclusion

Not classified for mutagenic or genotoxic toxicity

#### Carcinogenicity

### BIKE7 LUBRICATE DRY

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation								Data waiving
Dermal								Data waiving
Oral								Data waiving

hydrocarbons, C6, isoalkanes, < 5% n-hexane

F	Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
e	exposure								
Ī	nhalation	NOAEC	Equivalent to	9016 ppm	104 weeks (6h / day,	Rat (male /	No carcinogenic		Experimental value
(	vapours)		OECD 451		5 days / week)	female)	effect		

n-hexane

Route of	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
exposure								
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	3000 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	No carcinogenic effect		Read-across
Inhalation (vapours)	LOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (female)	Tumor formation	Liver	Read-across
Inhalation (vapours)	NOAEC	Equivalent to OECD 451	9018 ppm	104 weeks (6h / day, 5 days / week)	Mouse (male)	No carcinogenic effect		Read-across

# Conclusion

Not classified for carcinogenicity

## Reproductive toxicity

# BIKE7 LUBRICATE DRY

No (test)data on the mixture available

Judgement is based on the relevant ingredients <u>hydrocarbons</u>, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Exposure time	Species	Effect	- 0	Value determination
Developmental toxicity	NOAEL	Equivalent to OECD 414	31680 mg/m³ air	10 days (6h / day)	Mouse	No effect		Read-across
Maternal toxicity	NOAEL	Equivalent to OECD 414	10560 mg/m³ air	10 days (6h / day)	Rat (female)	No effect		Read-across
	LOAEL	Equivalent to OECD 414	31680 mg/m³ air	10 days (6h / day)	Rat (female)	Lung tissue affection/degen eration	Lungs	Read-across
Effects on fertility	NOAEL (P/F1)	Equivalent to OECD 416	31680 mg/m³ air		Rat (male / female)	No effect		Read-across

hydrocarbons, C6, isoalkanes, < 5% n-hexane

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value
								determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	> 7000 ppm	10 days (6h / day)	Rat	No effect		Read-across
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	2000 ppm	10 days (6h / day)	Rat (female)	No effect		Read-across
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm		Rat (male / female)	No effect		Read-across

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14 Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 9/16

<u>n-hexane</u>

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
Maternal toxicity (Inhalation (vapours))	NOAEC	Equivalent to OECD 414	3000 ppm	10 days (gestation, 6h / day)	Rat	No effect		Experimental value
	LOAEC	Equivalent to OECD 414	9000 ppm	10 days (gestation, 6h / day)	Rat	Maternal toxicity		Experimental value
Effects on fertility (Inhalation (vapours))	NOAEC	Equivalent to OECD 416	9000 ppm	≥ 13 weeks (6h / day, 5 days / week)	Rat (male / female)	No effect		Experimental value

Classification of this substance according to Annex VI is debatable as it does not correspond to the conclusion from the test

Not classified for reprotoxic or developmental toxicity

# Toxicity other effects

BIKE7 LUBRICATE DRY

hydrocarbons, C6, isoalkanes, < 5% n-hexane

Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value
							determination
NOAEC	Equivalent to	9000 ppm	Central nervous	Overall effects	13 weeks (6h /	Rat (male /	Experimental
	OECD 424		system		day, 5 days /	female)	value
					week)		Inhalation

#### Chronic effects from short and long-term exposure

BIKE7 LUBRICATE DRY

No effects known.

#### 11.2. Information on other hazards

No evidence of endocrine disrupting properties

# SECTION 12: Ecological information

#### 12.1. Toxicity

BIKE7 LUBRICATE DRY

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LL50	OECD 203	> 13.4 mg/l WAF	96 h	Oncorhynchus mykiss	Semi-static system	Fresh water	Experimental value; Nominal concentration
Acute toxicity crustacea	EL50	OECD 202	3.0 mg/l WAF	48 h	Daphnia magna	Static system	Fresh water	Experimental value; GLP
Toxicity algae and other aquatic plants	EL50	OECD 201	13 mg/l WAF	96 h	Pseudokirchneri ella subcapitata	Static system	Fresh water	Read-across; GLP
Long-term toxicity fish	NOELR		1.534 mg/l	28	Oncorhynchus mykiss		Fresh water	QSAR; Nominal concentration
Toxicity aquatic micro- organisms	EL50		26.81 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth rate

<u>hydrocarbons, C6, isoalkanes, < 5% n-hexane</u>

	Parameter	Method	Value	Duration	Species		Fresh/salt water	Value determination
Acute toxicity fishes	LL50		18.27 mg/l	96 h	Oncorhynchus mykiss		Fresh water	QSAR
Acute toxicity crustacea	EL50		31.9 mg/l	48 h	Daphnia magna		Fresh water	QSAR
Toxicity algae and other aquatic plants	EL50		13.56 mg/l	72 h	Pseudokirchneri ella subcapitata		Fresh water	QSAR
Long-term toxicity fish	NOELR		4.089 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	QSAR
Long-term toxicity aquatic crustacea	NOELR		7.138 mg/l	21 day(s)	Daphnia magna		Fresh water	QSAR

Classification of this substance is debatable as it does not correspond to the conclusion from the test

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14 Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 10 / 16

<u>n-hexane</u>

exame								
	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LL50		12.51 mg/l	96 h	Oncorhynchus mykiss		Fresh water	Estimated value; Lethal
Acute toxicity crustacea	EL50		21.85 mg/l	48 h	Daphnia magna		Fresh water	Estimated value; Locomotor effect
Toxicity algae and other aquatic plants	EL50		9.285 mg/l	72 h	Pseudokirchneri ella subcapitata		Fresh water	Estimated value; Growth rate
Long-term toxicity fish	NOELR		2.8 mg/l	28 day(s)	Oncorhynchus mykiss		Fresh water	Estimated value; Growth rate
Long-term toxicity aquatic crustacea	NOELR		4.888 mg/l	21 day(s)	Daphnia magna		Fresh water	Estimated value; Reproduction
Toxicity aquatic micro- organisms	EL50		48.39 mg/l	48 h	Tetrahymena pyriformis		Fresh water	QSAR; Growth

### Conclusion

Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Experimental value

hydrocarbons, C6, isoalkanes, < 5% n-hexane

**Biodegradation water** 

Method	Value	Duration	Value determination
OECD 301F	98 %; GLP	28 day(s)	Read-across

n-hexane

Biodegradation water

Method	Value	Duration	Value determination
OECD 301F	98 %; Oxygen consumption	28 day(s)	Read-across

**Biodegradation soil** 

Method	Value	Duration	Value determination
			Data waiving

# Conclusion

Water

Contains readily biodegradable component(s)

# 12.3. Bioaccumulative potential

BIKE7 LUBRICATE DRY

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Log Kow

Method	Remark	Value	Temperature	Value determination
		> 3		

hydrocarbons, C6, isoalkanes, < 5% n-hexane

**BCF** fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		501.187		Pimephales promelas	Calculated value

Log Kow

Method	Remark	Value	Temperature	Value determination
Equivalent to OECD 107		3.34	20 °C	Read-across

n-hexane

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF	Other	501.187		Pimephales promelas	QSAR

Log Kow

-0 ·····									
Method	Remark	Value	Temperature	Value determination					
Equivalent to OECD 107		4	20 °C	Experimental value					

#### Conclusion

Contains bioaccumulative component(s)

# 12.4. Mobility in soil

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14

Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 11 / 16

#### hydrocarbons, C6, isoalkanes, < 5% n-hexane

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	Calculated value

#### Percent distribution

Method	Fraction air		Fraction sediment			Value determination	
Mackay level III	93.6 %	0 %	2.1 %	0.5 %	3.8 %	Calculated value	

#### n-hexane

#### (log) Koc

Parameter	Method	Value	Value determination
log Koc		3.34	QSAR

#### Conclusion

Contains component(s) that adsorb(s) into the soil

#### 12.5. Results of PBT and vPvB assessment

Due to insufficient data no statement can be made whether the component(s) fulfil(s) the criteria of PBT and vPvB according to Annex XIII of Regulation (EC) No 1907/2006.

# 12.6. Endocrine disrupting properties

No evidence of endocrine disrupting properties

#### 12.7. Other adverse effects

#### BIKE7 LUBRICATE DRY

#### **Greenhouse** gases

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014)

#### Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

# **SECTION 13: Disposal considerations**

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

#### **European Union**

Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997. Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

13 02 06\* (waste engine, gear and lubricating oils: synthetic engine, gear and lubricating oils). Depending on branch of industry and production process, also other waste codes may be applicable.

#### 13.1.2 Disposal methods

Refer to manufacturer/supplier for information on recovery/ recycling. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment. Dispose of at authorized waste collection point.

### 13.1.3 Packaging/Container

#### European Union

. Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

# **SECTION 14: Transport information**

## Road (ADR)

14.1. UN number					
UN number	1950				
14.2. UN proper shipping name					
Proper shipping name	aerosols				
14.3. Transport hazard class(es)					
Hazard identification number					
Class	2				
Classification code	5F				
14.4. Packing group					
Packing group					
Labels	2.1				
14. <u>5. Environmental hazards</u>					
Environmentally hazardous substance mark	no				
14. <u>6. Special precautions for user</u>					
Special provisions	190				
Special provisions	327				

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2006-12-14

Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 12 / 16

	BIKE7	LUBRICATE DRY
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
	Limited quantities	liquids. A package shall not weigh more than 30 kg. (gross mass)
ail (I	RID)	
14.	1. UN number	
	UN number	1950
14	2. UN proper shipping name	
	Proper shipping name	aerosols
	3. Transport hazard class(es)	
	Hazard identification number	23
	Class	2
	Classification code	5F
,	4. Packing group	
	Packing group	
	Labels	2.1
1.1		Z.1
	5. Environmental hazards	
	Environmentally hazardous substance mark	no
14.	6. Special precautions for user	100
	Special provisions	190
	Special provisions	327
	Special provisions	344
	Special provisions	625
	Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
land	d waterways (ADN)	
14.	1. UN number	
	UN number	1950
14.	2. UN proper shipping name	<u> </u>
	Proper shipping name	aerosols
	3. Transport hazard class(es)	
	Class	2
	Classification code	5F
	4. Packing group	
	Packing group	
	Labels	2.1
1/1	5. Environmental hazards	L-1-1
	Environmentally hazardous substance mark	no
	6. Special precautions for user	
	Special provisions	190
	Special provisions	327
		344
	Special provisions	625
	Special provisions Limited quantities	Combination packagings: not more than 1 liter per inner packaging for
, , (ı	MDG/IMSBC)	liquids. A package shall not weigh more than 30 kg. (gross mass)
	1. UN number	
	UN number	1950
	2. UN proper shipping name	
	Proper shipping name	aerosols
14.	3. Transport hazard class(es)	
	Class	2.1
14.	4. Packing group	
	Packing group	
	Labels	2.1
14.	5. Environmental hazards	
	Marine pollutant	Р
	Environmentally hazardous substance mark	no
	6. Special precautions for user	
		190
14.	Special provisions	
14.	Special provisions Special provisions	277
14.	Special provisions	
14.	Special provisions Special provisions	327
14.	Special provisions Special provisions Special provisions	327 344
14.	Special provisions Special provisions Special provisions Special provisions	327 344 381
14.	Special provisions Special provisions Special provisions Special provisions Special provisions	327 344 381 63
14.	Special provisions Special provisions Special provisions Special provisions	327 344 381

Reason for revision: 2, 3, 8, 9, 12

Publication date: 2006-12-14

Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 13 / 16

14.7. Maritime transport in bulk according to IMO instruments						
Annex II of MARPOL 73/78	Not applicable					
Air (ICAO-TI/IATA-DGR)						
14.1. UN number						
UN number	1950					
14.2. UN proper shipping name						
Proper shipping name	aerosols, flammable					
14.3. Transport hazard class(es)						
Class	2.1					
14.4. Packing group						
Packing group						
Labels	2.1					
14. <u>5. Environmental hazards</u>						
Environmentally hazardous substance mark	no					
14. <u>6. Special precautions for user</u>						
Special provisions	A145					
Special provisions	A167					
Special provisions	A802					
Passenger and cargo transport						
Limited quantities: maximum net quantity per packaging	30 kg G					

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
45.07 %	
339.492 g/l	

#### **REACH Annex XVII - Restriction**

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

and use of certain dangerous substances, mixtures and articles.							
	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction					
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics     hydrocarbons, C6, isoalkanes, < 5% n-hexane     n-hexane	Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	1. Shall not be used in:  — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,  — tricks and jokes,  — games for one or more participants, or any article intended to be used as such, even with ornamental aspects,  2. Articles not complying with paragraph 1 shall not be placed on the market.  3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  — can be used as fuel in decorative oil lamps for supply to the general public, and,  — present an aspiration hazard and are labelled with H304,  4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage";  b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage";  c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.					
hydrocarbons, C7, n-alkanes, isoalkanes, cyclics     hydrocarbons, C6, isoalkanes, < 5% n-hexane     n-hexane	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not.	1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:  — metallic glitter intended mainly for decoration,  — artificial snow and frost,  — "whoopee" cushions,  — silly string aerosols,  — imitation excrement,  — horns for parties,  — decorative flakes and foams,  — artificial cobwebs,  — stink bombs.  2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is					

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14
Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 14 / 16

		marked visibly, legibly and indelibly with:
		"For professional users only".
		3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers
		referred to Article 8 (1a) of Council Directive 75/ 324/EEC.
		4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the
		market unless they conform to the requirements indicated.
· n-hexane	Substances falling within one or more of the following points:  (a) substances classified as any of the	Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081
	following in Part 3 of Annex VI to Regulation (EC) No 1272/2008:	
	— carcinogen category 1A, 1B or 2, or germ	
	cell mutagen category 1A, 1B or	
	2, but excluding any such substances classified	
	due to effects only following	
	exposure by inhalation	
	— reproductive toxicant category 1A, 1B or 2	
	but excluding any such substances classified	
	due to effects only following exposure by	
	inhalation	
	— skin sensitiser category 1, 1A or 1B	
	— skin corrosive category 1, 1A, 1B or 1C or	
	skin irritant category 2	
	— serious eye damage category 1 or eye	
	irritant category 2	
	(b) substances listed in Annex II to Regulation	
	(EC) No 1223/2009 of the European	
	Parliament and of the Council	
	(c) substances listed in Annex IV to Regulation	
	(EC) No 1223/2009 for which a condition is	
	specified in at least one of the columns g, h	
	and i of the table in that Annex (d) substances	
	listed in Appendix 13 to this Annex.	
	The ancillary requirements in paragraphs 7	
	and 8 of column 2 of this entry apply to all	
	mixtures for use for tattooing purposes,	
	whether or not they contain a substance	
	falling within points (a) to (d) of this column of	
	this entry.	
	· ·	
	l .	

# National legislation Belgium BIKE7 LUBRICATE DRY

No data available

#### **National legislation The Netherlands**

В	II	K	E	7	L	ũ	ΙB	R	IC	Α	Т	E	DR	Υ

	Waterbezwaarlijkheid	Z (2); Algemene Beoordelingsmethodiek (ABM)
<u>n</u>	<u>-hexane</u>	
	SZW - Lijst van voor de	n-hexaan; Opgenomen in SZW-lijst van voor de voortplanting giftige stoffen (vruchtbaarheid); 2
	voortplanting giftige stoffen	
	(vruchtbaarheid)	

# National legislation France BIKE7 LUBRICATE DRY

No data available

<u>n-hexane</u>

Catégorie toxique pour la n-Hexane; R2 reproduction

# National legislation Germany BIKE7 LUBRICATE DRY

	Lagerklasse (TRGS510)	2B: Aerosolpackungen und Feuerzeuge	
	WGK	1; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017	
<u>h</u>	hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
	TA-Luft	5.2.5/I	
hydrocarbons, C6, isoalkanes, < 5% n-hexane			
[	TA-Luft	5.2.5/I	
<u>n-hexane</u>			
	TA-Luft	5.2.5/I	
Ī	TRGS900 - Risiko der	n-Hexan; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen	
	Fruchtschädigung	Grenzwertes nicht befürchtet zu werden	

# National legislation United Kingdom BIKE7 LUBRICATE DRY

No data available

# Other relevant data BIKE7 LUBRICATE DRY

No data available

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14

Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 15 / 16

n-hexane

TLV - Skin absorption n-Hexane; Skin; Danger of cutaneous absorption

#### 15.2. Chemical safety assessment

No chemical safety assessment has been conducted for the mixture.

### SECTION 16: Other information

#### Full text of any H- and EUH-statements referred to under section 3:

H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility.

H373 May cause damage to organs (central nervous system) through prolonged or repeated exposure if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

(\*) INTERNAL CLASSIFICATION BY BIG

ADI Acceptable daily intake

AOEL Acceptable operator exposure level

ATE Acute Toxicity Estimate

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

DMEL Derived Minimal Effect Level
DNEL Derived No Effect Level
EC50 Effect Concentration 50 %

ErC50 EC50 in terms of reduction of growth rate

LC50 Lethal Concentration 50 %

LD50 Lethal Dose 50 %

NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration

OECD Organisation for Economic Co-operation and Development

PBT Persistent, Bioaccumulative & Toxic
PNEC Predicted No Effect Concentration
STP Sludge Treatment Process

vPvB very Persistent & very Bioaccumulative

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2, 3, 8, 9, 12 Publication date: 2006-12-14
Date of revision: 2021-06-19

Revision number: 0400 BIG number: 44633 16 / 16